



Clevis Sling Hook With Latch Cartec CBX

Product information

Clevis sling hook with latch grade 100, forged from high-strength alloy steel. Designed for quick and secure suspension of slings, chains, or fittings, it ensures reliable load engagement and smooth operation under heavy-duty conditions.

Features:

- Grade 100 strength for demanding lifting tasks
- Secure latch prevents accidental sling disengagement
- Precision-forged for optimal load distribution and durability
- Wide compatibility with chain and sling systems

Material: Alloy steel

Marking: CE-marked

Temperature range: -40°C up to +200°C without reduction in WLL

Finish: Powder coated

Safety factor: 4:1

Grade: 10

Part code	Chain diameter in	WLL lb	Chain diameter mm	WLL (metric) tonnes	A mm	A1 mm	B mm	C mm	G mm	H mm	R mm	PxL mm	Weight kg
402300141890	1/4	3,000	6	1.4	26	19	7	8	15	20	69	7.5x17.5	0.31
402300191890	9/32	4,300	7	1.9	34	26	9.5	10	19	28	95	9x22.5	0.64
402300251890	5/16	5,700	8	2.5	34	26	9.5	10	19	28	95	10x22.5	0.61
402300401890	3/8	8,800	10	4	40	31	12	13.5	25	33	110	13x29.5	1.17
402300671890	1/2	15,000	13	6.7	51	40	15	17	30	40	136	16x37	2.11
402301001890	5/8	22,600	16	10	56	45	18	22	37	48	155	20x52	3.48
402301601890	3/4	35,300	20	16	60	53	23	26	51	52	185	24x73	6.8
402301901890	7/8	42,700	22	19	70	62	26	29	50	63	210	26x72	9.11

Blueprint

