



Clevis Sling Hook With Latch Cartec CBX

Product information



Clevis sling hook with latch grade 100, forged from high-strength alloy steel. Designed for quick and secure suspension of slings, chains, or fittings, it ensures reliable load engagement and smooth operation under heavy-duty conditions.

Features:

- Grade 100 strength for demanding lifting tasks
- Secure latch prevents accidental sling disengagement
- Precision-forged for optimal load distribution and durability
- Wide compatibility with chain and sling systems

... [Read more](#)

Material: Alloy steel

Marking: CE-marked

Temperature range: -40°C up to +200°C without reduction in WLL

Finish: Powder coated


Safety factor: 4:1

Grade: 10



Clevis Sling Hook With Latch Cartec CBX

Blueprint



Technical data

Part code	Chain diameter mm	Chain diameter in	WLL lb	A in	A1 in	B in	C in	G in	H in	R in	PxL in	Weight lb
-	6	1/4	3,000	1.02	0.75	0.28	0.31	0.59	0.79	2.72	0.3	0.68
6830578	7	9/32	4,300	1.34	1.02	0.37	0.39	0.75	1.1	3.74	0.35	1.41
-	8	5/16	5,700	1.34	1.02	0.37	0.39	0.75	1.1	3.74	0.39	1.34
-	10	3/8	8,800	1.57	1.22	0.47	0.53	0.98	1.3	4.33	0.51	2.58
-	13	1/2	15,000	2.01	1.57	0.59	0.67	1.18	1.57	5.35	0.63	4.65
-	16	5/8	22,600	2.2	1.77	0.71	0.87	1.46	1.89	6.1	0.79	7.67
-	20	3/4	35,300	2.36	2.09	0.91	1.02	2.01	2.05	7.28	0.94	14.99
-	22	7/8	42,700	2.76	2.44	1.02	1.14	1.97	2.48	8.27	1.02	20.08