



LAM-É
ST-PIERRE

Lifting Solutions Group
Axel Johnson International

Eye Sling Hook Cartec with Forged Latch CAX

Product information



Eye sling hook with forged latch CAX designed for grade 100 lifting applications. Features a robust eye for easy connection to master links or slings and a secure latch that closes automatically under load to prevent accidental disengagement. Built from high-strength alloy steel for exceptional durability and reliability in heavy-duty lifting operations. Suitable for chain sling assemblies in construction, industrial rigging, and material handling environments. Available in multiple sizes to accommodate a wide range of working load limits.

Material: Alloy steel

Marking: CE-marked

Temperature range: -40°C up to +200°C without reduction in WLL

Finish: Powder coated

Safety factor: 4:1

Grade: 10

Part code	Chain diameter in	WLL lb	Chain diameter mm	WLL (metric) tonnes	A mm	A1 mm	D mm	G mm	H mm	O mm	R mm	Weight kg
402300142310	1/4	3,000	6	1.4	26	19	10	16	20	20	81	0.25
402300252310	9/32-5/16	5,700	7-8	2.5	33	26	11	19	29	25	101	0.5
402300402310	3/8	8,800	10	4	40	31	16	26	33	34	131	0.97
402300672310	1/2	15,000	13	6.7	51	40	19	33	42	43	159	1.9
402301002310	5/8	22,600	16	10	56	45	24.5	40	50	50	183	3.3
402301602310	3/4	35,300	20	16	60	52	27	48	53	55	203	4.5
402301902310	7/8	42,700	22	19	70	62	29	50	60	60	224	7.1
402302652310	1	59,700	26	26.5	77	73	35	60	75	70	257	12
402304002310	1 1/4	90,400	32	40	102	94	42	73	91	84	335	27.7

Blueprint

