



Eye Sling Hook Cartec with Forged Latch CAX

Product information



Eye sling hook with forged latch CAX designed for grade 100 lifting applications. Features a robust eye for easy connection to master links or slings and a secure latch that closes automatically under load to prevent accidental disengagement. Built from high-strength alloy steel for exceptional durability and reliability in heavy-duty lifting operations. Suitable for chain sling assemblies in construction, industrial rigging, and material handling environments. Available in multiple sizes to accommodate a wide range of working load limits.

... [Read more](#)

Material: Alloy steel

Marking: CE-marked

Temperature range: -40°C up to +200°C without reduction in WLL

Finish: Powder coated


Safety factor: 4:1

Grade: 10



Eye Sling Hook Cartec with Forged Latch CAX

Blueprint



Technical data

Part code	Chain diameter in	WLL lb	A in	A1 in	D in	G in	H in	O in	R in	A1 in	Weight lb
402300142310	1/4	3,000	1.02	0.75	0.39	0.63	0.79	0.79	3.19	-	0.55
402300252310	9/32-5/16	5,700	1.3	-	0.43	0.75	1.14	0.98	3.98	1.02	1.1
402300402310	3/8	8,800	1.57	-	0.63	1.02	1.3	1.34	5.16	1.22	2.14
402300672310	1/2	15,000	2.01	-	0.75	1.3	1.65	1.69	6.26	1.57	4.19
402301002310	5/8	22,600	2.2	-	0.96	1.57	1.97	1.97	7.2	1.77	7.28
402301602310	3/4	35,300	2.36	-	1.06	1.89	2.09	2.17	7.99	2.05	9.92
402301902310	7/8	42,700	2.76	-	1.14	1.97	2.36	2.36	8.82	2.44	15.65
402302652310	1	59,700	3.03	-	1.38	2.36	2.95	2.76	10.12	2.87	26.46
402304002310	1 1/4	90,400	4.02	-	1.65	2.87	3.58	3.31	13.19	3.7	61.07