



Eye Sling Hook with Forged Latch CAX



Product information

Eye sling hook with forged latch CAX designed for grade 100 lifting applications. Features a robust eye for easy connection to master links or slings and a secure latch that closes automatically under load to prevent accidental disengagement. Built from high-strength alloy steel for exceptional durability and reliability in heavy-duty lifting operations. Suitable for chain sling assemblies in construction, industrial rigging, and material handling environments. Available in multiple sizes to accommodate a wide range of working load limits.

Marking: CE-marked

Safety factor: 4:1

Grade: 10

Part code	Chain diameter in	WLL lbs	Chain diameter mm	WLL (metric) tonnes	A mm	A1 mm	D mm	G mm	H mm	O mm	R mm	Weight kg
		lbs										
402300142310	1/4	3,000	6	1.4	26	19	10	16	20	20	81	0.25
402300252310	9/32-5/16	5,700	7-8	2.5	33	26	11	19	29	25	101	0.5
402300402310	3/8	8,800	10	4	40	31	16	26	33	34	131	0.97
402300672310	1/2	15,000	13	6.7	51	40	19	33	42	43	159	1.9
402301002310	5/8	22,600	16	10	56	45	24.5	40	50	50	183	3.3
402301602310	3/4	35,300	20	16	60	52	27	48	53	55	203	4.5
402301902310	7/8	42,700	22	19	70	62	29	50	60	60	224	7.1
402302652310	1	59,700	26	26.5	77	73	35	60	75	70	257	12
402304002310	1 1/4	90,400	32	40	102	94	42	73	91	84	335	27.7

Blueprint

