



LAM-É
ST-PIERRE

Lifting Solutions Group
Axel Johnson International

Eye Sling Hook Cartec with Forged Latch CAX

Product information



Eye sling hook with forged latch CAX designed for grade 100 lifting applications. Features a robust eye for easy connection to master links or slings and a secure latch that closes automatically under load to prevent accidental disengagement. Built from high-strength alloy steel for exceptional durability and reliability in heavy-duty lifting operations. Suitable for chain sling assemblies in construction, industrial rigging, and material handling environments. Available in multiple sizes to accommodate a wide range of working load limits.

Material: Alloy steel

Marking: CE-marked

Temperature range: -40°C up to +200°C without reduction in WLL

Finish: Powder coated

Safety factor: 4:1

Grade: 10

Part code	Chain diameter in	WLL lb	A in	A1 in	D, in	G, in	H, in	Omm in	Rmm in	A1 in	Weight lb
402300142310	1/4	3,000	1.02	0.75	0.39	0.63	0.79	0.79	3.19	-	0.55
402300252310	9/32-5/16	5,700	1.3	-	0.43	0.75	1.14	0.98	3.98	1.02	1.1
402300402310	3/8	8,800	1.57	-	0.63	1.02	1.3	1.34	5.16	1.22	2.14
402300672310	1/2	15,000	2.01	-	0.75	1.3	1.65	1.69	6.26	1.57	4.19
402301002310	5/8	22,600	2.2	-	0.96	1.57	1.97	1.97	7.2	1.77	7.28
402301602310	3/4	35,300	2.36	-	1.06	1.89	2.09	2.17	7.99	2.05	9.92
402301902310	7/8	42,700	2.76	-	1.14	1.97	2.36	2.36	8.82	2.44	15.65
402302652310	1	59,700	3.03	-	1.38	2.36	2.95	2.76	10.12	2.87	26.46
402304002310	1 1/4	90,400	4.02	-	1.65	2.87	3.58	3.31	13.19	3.7	61.07

Blueprint

