



Clevis Grab Hook with Saddle CFX-CFX S

Product information

Clevis grab/shortening hook with saddle CFX-CFX S, offered in two variants—without latch (CFX) and with latch (CFXS)—designed for Grade 100 lifting systems. Featuring a clevis-style connection for direct chain attachment and a contoured cradle to support chain links under load, it ensures accurate alignment and minimizes wear. This hook adapts to various sling assemblies—single-leg, multi-leg or applications requiring load restraint and length adjustment.

Features:

- Suitable for chain sizes between 6mm and 22 mm ($\frac{1}{4}''$ – $\frac{7}{8}''$)
- Available in both compact and latch-equipped configurations.

Marking: CE-marked

Safety factor: 4:1

Grade: 10

Part code	Chain diameter in	WLL lbs	Chain diameter mm	WLL (metric) tonnes	A mm	B mm	C mm	G mm	H mm	R mm	M mm	PxL mm	Weight kg
lbs													
402300142270	1/4	3,000	6	1.4	8	7.5	8.8	22	22	51.5	35.5	7.5x17.5	0.2
402300192270	9/32	4,300	7	1.9	10	10	11.4	30	28	66.5	47	9x22.5	0.44
402300252270	5/16	5,700	8	2.5	10	10	10.9	30	28	66	47	10x22.5	0.44
402300402270	3/8	8,800	10	4	13	13	15	44	34	79.9	55	13x31.5	0.96
402300672270	1/2	15,000	13	6.7	17	16	17.5	53	47	105.4	81	16x42	2.1
402301002270	5/8	22,600	16	10	19	19	18.3	64	60	111.8	92	21x51.5	3.4
402301602270	3/4	35,300	20	16	23.5	23	22	85	65	118	100	24x61.5	5.2
402301902270	7/8	42,700	22	19	26	26	25	92	68	154	120	26x72	7.8

Blueprint

