



Clevis Grab Hook with Saddle Cartec CFX-CFX S

Product information



Clevis grab/shortening hook with saddle CFX-CFX S, offered in two variants—without latch (CFX) and with latch (CFX-S)—designed for Grade 100 lifting systems. Featuring a clevis-style connection for direct chain attachment and a contoured cradle to support chain links under load, it ensures accurate alignment and minimizes wear. This hook adapts to various sling assemblies—single-leg, multi-leg or applications requiring load restraint and length adjustment.

Features:

- Suitable for chain sizes between 6mm and 22 mm (1/4"–7/8")
- Available in both compact and latch-equipped configurations.

... [Read more](#)

Material: Alloy steel

Marking: CE-marked

Temperature range: -40°C up to +200°C without reduction in WLL

Finish: Powder coated


Safety factor: 4:1

Grade: 10



Clevis Grab Hook with Saddle Cartec CFX-CFX S

Blueprint



Technical data

Part code	Chain diameter mm	Chain diameter in	WLL lb	A in	B in	C in	G in	H in	R in	M in	PxL in	Weight lb
142270	6	1/4	3,000	0.31	0.3	0.35	0.87	0.87	2.03	1.4	0.3	0.44
-	7	9/32	4,300	0.39	0.39	0.45	1.18	1.1	2.62	1.85	0.35	0.97
-	8	5/16	5,700	0.39	0.39	0.43	1.18	1.1	2.6	1.85	0.39	0.97
-	10	3/8	8,800	0.51	0.51	0.59	1.73	1.34	3.15	2.17	0.51	2.12
-	13	1/2	15,000	0.67	0.63	0.69	2.09	1.85	4.15	3.19	0.63	4.63
-	16	5/8	22,600	0.75	0.75	0.72	2.52	2.36	4.4	3.62	0.83	7.5
-	20	3/4	35,300	0.93	0.91	0.87	3.35	2.56	4.65	3.94	0.94	11.46
-	22	7/8	42,700	1.02	1.02	0.98	3.62	2.68	6.06	4.72	1.02	17.2