



Clevis Self Locking Hook Cartec CRFX

Product information



Clevis self-locking hook grade 100 for chain sling assemblies, engineered to lock automatically under load for secure, accident-resistant engagement. Direct clevis connection enables quick attachment to chain without a coupling link, supporting durable, heavy-duty use.

Features:

- Self-locking latch closes automatically when load is applied, helping prevent accidental opening.
- Clevis head attaches directly to chain for streamlined sling builds (no coupling link needed).
- Grade 100 construction for high strength in demanding lifting tasks.
- Available in multiple sizes and WLL ranges

... [Read more](#)

Material: Alloy steel

Marking: CE-marked

Temperature range: -40°C up to +200°C without reduction in WLL

Finish: Powder coated


Safety factor: 4:1

Grade: 10



Clevis Self Locking Hook Cartec CRFX

Blueprint



Technical data

Part code	Chain diameter mm	Chain diameter in	WLL	A in	B in	C in	G, in	H, in	Rmm in	T in	PxL in	Weight lb
402300141760	6	1/4	3,000	1.1	0.28	0.31	0.63	0.83	3.7	1.38	0.28	1.1
402300191760	7	9/32	4,300	1.34	0.35	0.39	0.79	1.02	4.84	1.69	0.35	2.09
402300251760	8	5/16	5,700	1.34	0.35	0.39	0.79	1.02	4.84	1.69	0.39	2.09
402300401760	10	3/8	8,800	1.77	0.47	0.55	0.98	1.18	5.63	2.2	0.51	3.53
402300671760	13	1/2	15,000	2.01	0.59	0.67	1.38	1.57	7.09	2.72	0.63	7.05
402301001760	16	5/8	22,600	2.36	0.75	0.75	1.42	1.97	8.46	3.15	0.83	13.23
402301601760	20	3/4	35,300	2.76	0.91	1.02	2.36	2.64	9.96	3.54	0.94	21.61
402301901760	22	7/8	42,200	3.23	1.02	1.26	2.44	2.76	11.3	3.94	1.02	31.75