



## Swivel Self Locking Hook Cartec CRGX



### Product information

Swivel self-locking hook CRGX designed for grade 100 lifting applications. Equipped with a 360° swivel and an automatic locking mechanism that engages under load, ensuring secure lifting and preventing accidental release. The swivel feature allows rotation to reduce chain twist and improve load positioning during operations. Built from high-strength alloy steel for durability and reliability in heavy-duty environments such as construction, industrial rigging, and material handling.

**Material:** Alloy steel

**Marking:** CE-marked

**Temperature range:** -40°C up to +200°C without reduction in WLL

**Finish:** Powder coated

**Safety factor:** 4:1

**Grade:** 10

Part code	Chain diameter in	WLL	Chain diameter mm	WLL (metric) tonnes	R mm	A mm	B mm	O mm	D mm	G mm	H mm	T mm	Weight kg
402300142350	1/4	3,000	6	1.4	160	28	27	36	13	16	21	35	0.6
402300252350	9/32-5/16	5,700	7-8	2.5	182	34	27	36	13	20	26	43	1.1
402300402350	3/8	8,800	10	4	217	45	35	45	16	25	30	56	2
402300672350	1/2	15,000	13	6.7	271	54	45	50	21	35	40	69	4
402301002350	5/8	22,600	16	10	320	62	58	62	24	38	50	80	6.8

# Blueprint

