



Lever Hoist KITO LB Series

Product information



The KITO LB leverhoist is built with premium grade components and makes it particularly suitable for continuous operation under most severe conditions.

Features:

- Standard supplied with a unique freewheel chain adjusting mechanism with overload protection.
- Rugged and ergonomic lever handle.
- Smooth geared mechanism for effortless handling.
- Robust mechanical load brake increases the safety of the operator.
- Double-reduction gearing requires minimum manual power for operation at full load.
- Open load sheave allows easy inspection and cleaning without dismantling the unit.
- Sealed gears and brake are protected against damage from dust and water.
- Fourfold riveted and forged carbon steel bottom hook.
- Abrasion-resistant nickel-plated load chain V(G100) for high and uniform strength (1000 N/mm²), in accordance with standard DIN EN 818-7.

Optional:

- Friction clutch
- Overload signal
- Wire rope clip
- Shipyard hooks
- Without freewheel mechanism

... [Read more](#)

Material: High grade Steel housing, nickel-plated load chain, Carbon steel hooks

Marking: According to standard, CE-marked

Standard: EN 13157


Warning: Minimum load is needed for the load pressure brake to work correct.

Safety factor: 4:1



Lever Hoist KITO LB Series

Blueprint



Technical data

Part code	Code	WLL (metric) tonnes	Lifting height m	Number of falls	Min. load kg	Load chain mm	A in	B in	C in	D in	e mm in	g mm in	S in	t in	Weight lb
16.20LB008S015	LB008S015	0.8	1.5	1	25	5.6 x 15.7	4.49	4.69	11.02	9.65	3.82	0.93	1.28	0.55	12.57
16.20LB008L015	LB008L015	0.8	1.5	1	25	5.6 x 15.7	4.49	4.69	11.02	9.65	3.82	0.93	1.28	0.55	12.57
16.20LB008O015	LB008O015	0.8	1.5	1	25	5.6 x 15.7	4.49	4.69	11.02	9.65	3.82	0.93	1.28	0.55	12.57
-	Without freewheel function (OF)	0.8	1.5	1	25	5.6 x 15.7	4.49	4.69	11.02	9.65	3.82	0.93	1.28	0.55	12.57
-	LB008S020	0.8	2	1	25	5.6 x 15.7	4.49	4.69	11.02	9.65	3.82	0.93	1.28	0.55	13.34
16.20LB008O030	LB008O030	0.8	3	1	25	5.6 x 15.7	4.49	4.69	11.02	9.65	3.82	0.93	1.28	0.55	14.88
16.20LB008S030	LB008S030	0.8	3	1	25	5.6 x 15.7	4.49	4.69	11.02	9.65	3.82	0.93	1.28	0.55	14.99
-	LB008S060	0.8	6	1	25	5.6 x 15.7	4.49	4.69	11.02	9.65	3.82	0.93	1.28	0.55	19.62
-	LB008S105	0.8	10.5	1	25	5.6 x 15.7	4.49	4.69	11.02	9.65	3.82	0.93	1.28	0.55	26.46
-	LB008	0.8	-	1	25	5.6 x 15.7	4.49	4.69	11.02	9.65	3.82	0.93	1.28	0.55	-
-	LB010S010	1	1	1	25	5.6 x 15.7	4.49	4.69	11.81	9.65	3.82	1.14	1.67	0.59	12.24
-	LB010S015	1	1.5	1	25	5.6 x 15.7	4.49	4.69	11.81	9.65	3.82	1.14	1.67	0.59	12.57
16.20LB010S015	LB010S015	1	1.5	1	25	5.6 x 15.7	4.49	4.69	11.81	9.65	3.82	1.14	1.67	0.59	13.01
-	LB010S020	1	2	1	25	5.6 x 15.7	4.49	4.69	11.81	9.65	3.82	1.14	1.67	0.59	13.78
16.20LB010S030	LB010S030	1	3	1	25	5.6 x 15.7	4.49	4.69	11.81	9.65	3.82	1.14	1.67	0.59	15.43
-	LB010O030	1	3	1	25	5.6 x 15.7	4.49	4.69	11.81	9.65	3.82	1.14	1.67	0.59	15.43
-	LB010S040	1	4	1	25	5.6 x 15.7	4.49	4.69	11.02	9.65	3.82	0.93	1.28	0.55	16.98
-	LB010S050	1	5	1	25	5.6 x 15.7	4.49	4.69	11.81	9.65	3.82	1.14	1.67	0.59	18.41
-	LB010S060	1	6	1	25	5.6 x 15.7	4.49	4.69	11.81	9.65	3.82	1.14	1.67	0.59	20.06
16.20LB016S015	LB016S015	1.6	1.5	1	38	7.1 x 19.9	6.26	4.96	13.19	10.43	3.94	1.26	1.67	0.75	17.64
-	LB016L015	1.6	1.5	1	38	7.1 x 19.9	6.26	4.96	13.19	10.43	3.94	1.26	1.67	0.75	17.64



Lever Hoist KITO LB Series

Technical data

Part code	Code	WLL (metric) tonnes	Lifting height m	Number of falls	Min. load kg	Load chain mm	A in	B in	C in	D in	e mm in	g mm in	S in	t in	Weight lb
-	LB016O015	1.6	1.5	1	38	7.1 x 19.9	6.26	4.96	13.19	10.43	3.94	1.26	1.67	0.75	17.64
-	LB016S020	1.6	2	1	38	7.1 x 19.9	6.26	4.96	13.19	10.43	3.94	1.26	1.67	0.75	18.85
-	LB016S025	1.6	2.5	1	38	7.1 x 19.9	6.26	4.96	13.19	10.43	3.94	1.26	1.67	0.75	20.06
16.20LB016O030	LB016O030	1.6	3	1	38	7.1 x 19.9	6.26	4.96	13.19	10.43	3.94	1.26	1.67	0.75	21.27
16.20LB016S030	LB016S030	1.6	3	1	38	7.1 x 19.9	6.26	4.96	13.19	10.43	3.94	1.26	1.67	0.75	21.38
-	LB016S040	1.6	4	1	38	7.1 x 19.9	6.26	4.96	13.19	10.43	3.94	1.26	1.67	0.75	23.7
-	LB016S050	1.6	5	1	38	7.1 x 19.9	6.26	4.96	13.19	10.43	3.94	1.26	1.67	0.75	26.12
-	LB016S060	1.6	6	1	38	7.1 x 19.9	6.26	4.96	13.19	10.43	3.94	1.26	1.67	0.75	28.66
-	LB016O060	1.6	6	1	38	7.1 x 19.9	6.26	4.96	13.19	10.43	3.94	1.26	1.67	0.75	28.66
16.20LB025S015	LB025S015	2.5	1.5	1	54	8.8 x 24.6	6.81	5.91	14.76	10.43	4.02	1.44	1.85	0.83	24.69
-	LB025O015	2.5	1.5	1	54	8.8 x 24.6	6.81	5.91	14.76	10.43	4.02	1.44	1.85	0.83	24.69
16.20LB025S030	LB025S030	2.5	3	1	54	8.8 x 24.6	6.81	5.91	14.76	10.43	4.02	1.44	1.85	0.83	30.42
-	LB025S060	2.5	6	1	54	8.8 x 24.6	6.81	5.91	14.76	10.43	4.02	1.44	1.85	0.83	41.67
-	LB025O060	2.5	6	1	54	8.8 x 24.6	6.81	5.91	14.76	10.43	4.02	1.44	1.85	0.83	41.67
16.20LB032S015	LB032S015	3.2	1.5	1	35	10.0 x 28.0	7.48	6.26	15.55	16.34	4.41	1.54	1.97	0.96	33.07
-	LB032L015	3.2	1.5	1	35	10.0 x 28.0	7.48	6.26	15.55	16.34	4.41	1.54	1.97	0.96	33.07
-	LB032O015	3.2	1.5	1	35	10.0 x 28.0	7.48	6.26	15.55	16.34	4.41	1.54	1.97	0.96	33.07
-	LB032S025	3.2	2.5	1	35	10.0 x 28.0	7.48	6.26	15.55	16.34	4.41	1.54	1.97	0.96	38.14
16.20LB032S030	LB032S030	3.2	3	1	35	10.0 x 28.0	7.48	6.26	15.55	16.34	4.41	1.54	1.97	0.96	40.79
-	LB032O030	3.2	3	1	35	10.0 x 28.0	7.48	6.26	15.55	16.34	4.41	1.54	1.97	0.96	40.79
-	LB032S050	3.2	5	1	35	10.0 x 28.0	7.48	6.26	15.55	16.34	4.41	1.54	1.97	0.96	50.82
-	LB032S060	3.2	6	1	35	10.0 x 28.0	7.48	6.26	15.55	16.34	4.41	1.54	1.97	0.96	56
-	LB032O060	3.2	6	1	35	10.0 x 28.0	7.48	6.26	15.55	16.34	4.41	1.54	1.97	0.96	56
-	LB032S100	3.2	10	1	35	10.0 x 28.0	7.48	6.26	15.55	16.34	4.41	1.54	1.97	0.96	76.17
16.20LB063S015	LB063S015	6.3	1.5	2	90	10.0 x 28.0	7.48	8.54	21.26	16.34	4.41	1.97	2.36	1.34	57.32
16.20LB063S030	LB063S030	6.3	3	2	90	10.0 x 28.0	7.48	8.54	21.26	16.34	4.41	1.97	2.36	1.34	72.97
-	LB063S060	6.3	6	2	90	10.0 x 28.0	7.48	8.54	21.26	16.34	4.41	1.97	2.36	1.34	104.06
-	LB063S080	6.3	8	2	90	10.0 x 28.0	7.48	8.54	21.26	16.34	4.41	1.97	2.36	1.34	124.67
-	LB063S100	6.3	10	2	90	10.0 x 28.0	7.48	8.54	21.26	16.34	4.41	1.97	2.36	1.34	145.39
16.20LB090S030	LB090S015	9	1.5	3	130	10.0 x 28.0	7.48	11.97	26.77	16.34	4.41	2.85	3.35	1.63	88.18
16.20LB090S030	LB090S030	9	3	3	130	10.0 x 28.0	7.48	11.97	26.77	16.34	4.41	2.85	3.35	1.63	111.33



Lever Hoist KITO LB Series

Technical data

Part code	Code	WLL (metric) tonnes	Lifting height m	Number of falls	Min. load kg	Load chain mm	A in	B in	C in	D in	e mm in	g mm in	S in	t in	Weight lb
-	LB090S035	9	3.5	3	130	10.0 x 28.0	7.48	11.97	26.77	16.34	4.41	2.85	3.35	1.63	119.05
16.20LB090S060	LB090S060	9	6	3	130	10.0 x 28.0	7.48	11.97	26.77	16.34	4.41	2.85	3.35	1.63	157.63