



## Turnbuckles Eye - Jaw Green Pin® G-6315

### Product information



The Green Pin® EJ Turnbuckle is a turnbuckle with eye-jaw end-fittings. The jaw is fitted with a safety bolt for sizes with a diameter thread up to 5/8" and fitted with a cotter pin for sizes with a diameter thread 3/4" and up. One of the unique features of Green Pin® Turnbuckles such as this one is that they can be used for both lifting and lashing. Galvanization of the Green Pin® EJ Turnbuckle ensures its long-term durability. The turnbuckle is available in a range with a diameter thread 3/8" (take up of 6") up to 2 3/4" (take up of 24").

Are equipped with pins and cotters.

Certification on request: 2.1, 2.2, 3.1, MTCa

**Standard:** generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b

[... Read more](#)

**Material:** drop forged high tensile steel SAE 1035 or 1045

**Marking:** CE-marked

**Temperature range:** -20°C up to +200°C

**Finish:** hot dipped galvanized


**Note:** jaw ends up to and including 5/8" are fitted with bolts and nuts, sizes 3/4" and up

**Safety factor:** 5:1



## Turnbuckles Eye - Jaw Green Pin® G-6315

Blueprint





## Turnbuckles Eye - Jaw Green Pin® G-6315

### Technical data

Part code	WLL (metric) tonnes	Thread Inch	Take up inch	a " in	b in	c in	d in	e in	f in	g in	h in	i in	j in	k in	l in	Weight lb
11.51SSGPGO1006	0.54	3/8	6	0.12	11.14	16.46	0.47	0.83	0.31	0.35	0.83	0.39	0.51	1.14	1.93	1.15
11.51SSGPGO1206	1	1/2	6	0.04	12.4	17.56	0.63	1.02	0.39	0.43	0.98	0.47	0.71	1.42	2.28	1.94
11.51SSGPGO1209	1	1/2	9	0.04	15.35	23.54	0.63	1.02	0.39	0.43	0.98	0.47	0.71	1.42	2.24	2.49
11.51SSGPGO1212	1	1/2	12	0.04	18.35	29.57	0.63	1.02	0.39	0.43	0.98	0.47	0.71	1.42	2.24	3.02
11.51SSGPGO1606	1.59	5/8	6	0.2	14.29	19.13	0.71	1.26	0.51	0.55	1.3	0.55	0.83	1.77	3.11	3.42
11.51SSGPGO1609	1.59	5/8	9	0.2	17.24	25.16	0.71	1.26	0.51	0.55	1.3	0.55	0.83	1.77	3.07	4.06
11.51SSGPGO1612	1.59	5/8	12	0.2	20.24	31.1	0.71	1.26	0.51	0.55	1.3	0.55	0.83	1.77	3.07	4.78
11.51SSGPGO1906	2.36	3/4	6	0.12	15.39	20.08	0.94	1.5	0.63	0.63	1.61	0.67	1.02	2.13	3.5	5.03
11.51SSGPGO1909	2.36	3/4	9	0.12	18.39	26.1	0.94	1.5	0.63	0.63	1.61	0.67	1.02	2.13	3.5	6.22
11.51SSGPGO1912	2.36	3/4	12	0.12	21.34	32.09	0.94	1.5	0.63	0.63	1.61	0.67	1.02	2.13	3.46	6.5
11.51SSGPGO1918	2.36	3/4	18	0.12	27.32	44.09	0.94	1.5	0.63	0.63	1.61	0.67	1.02	2.13	3.5	7.28
11.51SSGPGO2212	3.27	7/8	12	0.28	22.95	33.39	1.06	1.65	0.75	0.75	1.89	0.79	1.26	2.4	3.98	9.59
11.51SSGPGO2218	3.27	7/8	18	0.28	28.94	45.39	1.06	1.65	0.75	0.75	1.89	0.79	1.26	2.4	3.98	12.04
11.51SSGPGO2524	4.5	1	24	0.04	36.54	58.82	1.22	1.97	0.87	0.79	2.13	0.94	1.46	2.99	4.57	18.41
11.51SSGPGO2506	4.54	1	6	0.04	18.62	22.8	1.22	1.97	0.87	0.79	2.13	0.94	1.46	2.99	4.65	10.27
11.51SSGPGO2512	4.54	1	12	0.04	24.57	34.8	1.22	1.97	0.87	0.79	2.13	0.94	1.46	2.99	4.61	13.1
11.51SSGPGO2518	4.54	1	18	0.04	30.55	46.85	1.22	1.97	0.87	0.79	2.13	0.94	1.46	2.99	4.61	17.59
11.51SSGPGO3212	6.9	1 1/4	12	0.04	26.65	37.4	1.73	2.8	1.14	1.02	2.68	1.14	1.85	3.58	5.71	22.93
11.51SSGPGO3218	6.9	1 1/4	18	0.04	32.8	49.53	1.73	2.8	1.14	1.02	2.68	1.14	1.85	3.58	5.67	24.25
11.51SSGPGO3224	6.9	1 1/4	24	0.04	38.94	61.65	1.73	2.8	1.14	1.02	2.68	1.14	1.85	3.58	5.67	28.44
11.51SSGPGO3812	9.71	1 1/2	12	0.04	28.19	38.7	2.05	2.8	1.38	1.1	3.15	1.26	2.17	4.17	6.14	28.88
11.51SSGPGO3818	9.71	1 1/2	18	0.04	34.29	50.79	2.05	2.8	1.38	1.1	3.15	1.26	2.17	4.17	6.3	32.41
11.51SSGPGO3824	9.71	1 1/2	24	0.04	40.28	62.76	2.05	2.8	1.38	1.1	3.15	1.26	2.17	4.17	6.22	39.24
11.51SSGPGO4518	12.7	1 3/4	18	0.04	38.54	53.39	2.36	3.39	1.61	1.3	3.54	1.5	2.4	4.72	7.76	49.16
11.51SSGPGO4524	12.7	1 3/4	24	0.04	44.49	65.43	2.36	3.39	1.61	1.3	3.54	1.5	2.4	4.72	7.72	60.63
11.51SSGPGO5024	16.8	2	24	0.08	47.56	68.03	2.48	3.66	2.01	1.57	4.21	1.81	2.72	5.79	9.06	94.58
11.51SSGPGO6424	27.2	2 1/2	24	0.08	52.87	74.76	2.95	4.49	2.24	1.61	5.63	2.01	3.15	6.5	10.79	149.91
11.51SSGPGO6924	34	2 3/4	24	0.08	55.08	76.89	3.54	4.33	2.76	1.61	6.22	2.24	3.31	7.01	11.18	200.62