



Turnbuckles CP Jaw - Jaw Green Pin® Pin G-6313

Product information



The Green Pin® JJ Turnbuckle CP is a turnbuckle with jaw-jaw end-fittings and cotter pins, generally to ASTM F1145-92. One of the unique features of Green Pin® Turnbuckles such as this one is that they can be used for both lifting and lashing. Galvanization of the Green Pin® JJ Turnbuckle CP ensures its long-term durability. The turnbuckle is available in a range with a diameter thread of 3/4" (take up of 6") up to 2 3/4" (take up of 24").

Certification on request: 2.1, 2.2, 3.1, MTCa

Standard: Generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b

[... Read more](#)

Material: Drop forged high tensile steel SAE 1035 or 1045

Marking: CE-marked

Temperature range: -20°C up to +200°C


Finish: Hot dipped galvanized

Safety factor: 5:1



Turnbuckles CP Jaw - Jaw Green Pin® Pin G-6313

Blueprint



Technical data

Part code	Diameter mm	WLL (metric) tonnes	Thread Inch	Take up inch	a " in	b in	c in	d in	e in	f in	g in	h in	i in	Weight lb
11.51SSGPGG1906	41	2.36	3/4	6	0.12	14.53	19.17	17.28	0.94	1.5	0.63	0.63	1.61	5.71
11.51SSGPGG1909	41	2.36	3/4	9	0.12	17.48	25.2	20.24	0.94	1.5	0.63	0.63	1.61	6.9
11.51SSGPGG1912	41	2.36	3/4	12	0.12	20.47	31.18	23.23	0.94	1.5	0.63	0.63	1.61	7.54
11.51SSGPGG1918	41	2.36	3/4	18	0.12	26.38	43.15	29.13	0.94	1.65	0.63	0.63	1.61	9.94
11.51SSGPGG2212	48	3.27	7/8	12	0.28	22.09	32.52	25.12	1.06	1.65	0.75	0.75	1.89	10.87
11.51SSGPGG2218	48	3.27	7/8	18	0.28	28.07	44.57	31.1	1.06	1.65	0.75	0.75	1.89	14.13
11.51SSGPGG2506	54	4.54	1	6	0.04	17.6	21.81	20.94	1.22	3.66	0.87	0.79	2.13	11.42
11.51SSGPGG2512	54	4.54	1	12	0.04	23.54	33.82	26.89	1.22	3.66	0.87	0.79	2.13	14.18
11.51SSGPGG2518	54	4.54	1	18	0.04	29.53	45.98	32.87	1.22	3.66	0.87	0.79	2.13	18.52
11.51SSGPGG2524	54	4.54	1	24	0.04	35.55	57.87	38.9	1.22	1.97	0.87	0.79	2.13	19.62
11.51SSGPGG3212	68	6.9	1 1/4	12	0.04	25.24	35.98	29.45	1.73	2.8	1.14	1.02	2.68	24.69
11.51SSGPGG3218	68	6.9	1 1/4	18	0.04	31.61	48.35	35.83	1.73	2.8	1.14	1.02	2.68	29.98
11.51SSGPGG3224	68	6.9	1 1/4	24	0.04	37.87	60.59	42.09	1.73	2.8	1.14	1.02	2.68	33.07
11.51SSGPGG3812	80	9.71	1 1/2	12	0.04	26.57	37.09	31.73	2.05	2.8	1.38	1.1	3.15	37.48
11.51SSGPGG3818	80	9.71	1 1/2	18	0.04	32.48	48.98	37.64	2.05	2.99	1.38	1.1	3.15	42.55
11.51SSGPGG3824	80	9.71	1 1/2	24	0.04	38.58	61.06	43.74	2.05	2.99	1.38	1.1	3.15	45.64
11.51SSGPGG4518	90	12.7	1 3/4	18	0.04	36.93	51.81	42.99	2.36	3.39	1.61	1.3	3.54	55.12
11.51SSGPGG4524	90	12.7	1 3/4	24	0.04	42.87	63.82	48.94	2.36	3.39	1.61	1.3	3.54	63.27
11.51SSGPGG5024	107	16.8	2	24	0.08	45.31	65.79	52.68	2.48	3.66	2.01	1.57	4.21	100.09
11.51SSGPGG6424	143	27.2	2 1/2	24	0.08	49.41	72.09	58.27	2.95	4.49	2.24	1.61	5.63	194.01
11.51SSGPGG6924	158	34	2 3/4	24	0.08	53.07	74.09	63.15	3.54	4.33	2.76	1.61	6.22	216.05