



LAM-É
ST-PIERRE

Lifting Solutions Group
Axel Johnson International



DNV Master Link Assembly Van Beest Green Pin® P-6820

Product information

The Green Pin® DNV Master Link Assembly is perfect for offshore use. The Master Link Assembly is DNV-certified and has a large opening to accommodate larger lifting points. Moreover, the coating of the DNV Master Link Assembly ensures long-term durability, even under severe environmental conditions. The DNV Master Link Assembly is available in a range with a working load limit from 4.1 up to 100 ton.

Certification on request: 2.1, 2.2, 3.1, MTCb, MPIb, DNV 2.7-1a

Material: Alloy steel

Marking: According to standard

Temperature range: -40°C up to +200°C

Standard: DNV 2.7-1 Approved, EN 1677-4, EN 12079-2

Safety factor: 5:1

Grade: 8

Part code	WLL (metric) tonnes	a mmin	b mmin	c mmin	d mmin	e mmin	f mmin	Weight lb
401100410890	4.1	0.63	5.91	2.95	0.57	4.92	2.36	3.57
401100700890	7	0.87	10.63	5.51	0.87	6.38	3.54	11.51
401100930890	9.3	1.02	10.63	5.51	0.87	6.38	3.54	13.34
401101450890	14.5	1.1	10.63	5.51	0.87	6.38	3.54	14.84
401101900890	19	1.26	10.63	5.51	1.1	7.87	4.33	24.03
401102600890	26	1.42	10.63	5.51	1.1	7.87	4.33	27.34
401103050890	30.5	1.57	11.02	6.1	1.26	10.63	5.51	40.79
401104000890	40	1.77	12.6	6.89	1.42	10.63	5.51	55.34
401105100890	51	1.97	13.78	7.68	1.77	12.6	6.89	90.17
401107500890	75	2.56	16.14	8.66	1.97	13.78	7.68	145.73
401110000890	100	2.95	17.72	9.84	2.56	16.14	8.66	253.53

Blueprint

