



Pulling and Lifting Hoist, TIRFOR® TU

Product information



Portable hoist to lift and pull loads, for utilisation in numerous configurations with long cable lengths.

- Low weight - quick installation
- No limitation in terms of cable length
- Manageable, light-weight, robust, powerful
- Increase load capacity with deflection sheaves
- Overload protection
- Precise load placement within millimetres

[... Read more](#)

Marking: According to standard, Serial number and CE-marking.
Standard: EN 13157

Safety factor: 5:1



Pulling and Lifting Hoist, TIRFOR® TU

Technical data

Part code	Code	WLL (metric) tonnes	Lifting height m	Rope Ø mm	Dim. of the machine mm	Handle open/closed mm	Weight lb
501100080000110	TU-8	0.8	-	-	527 x 265 x 108	620 - 395	18.52
501100082000110	TU-8	0.8	20	8,3	527 x 265 x 108	620 - 395	34.17
501100160000110	TU-16	1.6	-	-	660 x 330 x 140	1190 - 680	39.68
501100162000110	TU-16	1.6	20	11,5	660 x 330 x 140	1190 - 680	73.85
501100320000110	TU-32	3.2	-	-	676 x 330 x 156	1190 - 680	59.52
501100322000110	TU-32	3.2	20	16,3	676 x 330 x 156	1190 - 680	123.46