LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Hydraulic Toe Jack Tractel HYDROFOR™

Product information

- Robust construction with a block steel body
- Ergonomic and removable handle for transport
- Working load applied on toe and head
- Pressure valve to avoid overloading
- Toe can swivel 360° around the axis of the jack
- Operation in both vertical and horizontal position.
- Easy maintenance
- Removable operating lever

... *Read more*

Marking: CE-mark
Warning: Do not use in unstable and uncertain positions. Never subject the toe to point loading, always fully load.

© November 2026 - All Rights Reserved

LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Hydraulic Toe Jack Tractel HYDROFOR™

Blueprint



Technical data

Part code	WLL (metric) tonnes	Hand force max. kg	Min–max lifting height of toe mm	Min–max lifting height of top mm	a in	b in	c in	d in	e in	f in	g in	Weight lb
16.35243269	5	38	25 - 230	368 - 573	14.49	29.13	5.51	8.39	ø 93	0.98	8.07	44.09
16.35243279	10	40	20 - 260	420 - 650	16.54	29.33	6.69	8.07	ø 103	1.18	9.06	61.73
16.3579909	25	40	58 - 273	505 - 720	19.88	51.38	8.27	16.54	6.1	2.28	8.46	240.3

© November 2026 - All Rights Reserved