LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Pulling Hoist, MINIFOR™

Product information



MINIFOR™ hoists are used with a Maxiflex wire rope. They can be used to lift or pull objects over great distances depending on the wire rope length. They are suitable for use in numerous configurations. They are operated through a pushbutton control. Optionally, the MINIFOR™ hoist can be equipped with a wire rope reeling device or a wireless remote control.

TR110 is fitted with an overload protection system

- Capacity 100 kg, 300 kg or 500 kg
- Quick installation
- Easy to use, light-weight, robust, powerful
- Available as single phase and three phase model
- Excellent capacity / weight ratio
- Unlimited wire rope travel
- Pendant control (up/down/emergency stop) 2,5 m
- Aluminium alloy design
- Swivelling suspension hook
- Protection: IP55 (Control: IP65)
- Upper and lower limit switches

Options:

- Special sleave block kits are available for all models (max. 980 kg). They enable doubling the capacity half the working speed
- Extension power supply and control cabel per m.
- Radio remote control
- Wire rope 10-100 m in 10 m. length interval. Other lengths on request
- Do only use original Minifor steel wire rope

... *Read more*


Marking: CE-mark, Load capacity, serial number.
Note: Excl. wire (to be ordered separately).

© November 2026 - All Rights Reserved

LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Pulling Hoist, MINIFOR™

Blueprint



Technical data

Part code	WLL (metric) tonnes	Lifting speed m/min	Type	WLL sheaved ton	Speed sheaved m/min	A in	B in	C in	D in	E in	F in	G in	H in	I in	J in	K in	L in	M in	Weight lb
16.28042789	0.1	15	TR10	0,2	7,5	16.81	0.79	5.51	24.84	8.23	4.41	0.79	0.79	12.76	14.02	4.49	0.59	-	44.09
16.28042889	0.3	5	TR30	0,6	2,5	16.81	0.79	5.51	24.84	8.23	4.41	0.79	0.79	12.76	14.02	4.49	0.59	-	44.09
16.28042989	0.3	13	TR30S	0,6	6,5	16.93	0.79	8.35	25.28	14.37	8.82	7.64	3.54	0.79	0.79	13.66	19.37	11.89	72.75
16.28044849	0.5	7	TR50	0,95	3,5	16.93	0.79	8.35	25.28	14.37	8.82	7.64	3.54	0.79	0.79	13.66	19.37	11.89	72.75

Type	Dimensions	Power supply*		Wire rope reeler		Radio					
	LxWxD mm	Single phase		Single phase		3 phase	20 m		27 m	40 m	control
115 Volt	230 Volt	400 Volt									
TR10	355x420x180	•		•			•		•	•	•
	•	•				•	•		•	•	
TR30	355x420x180	•		•			•		•	•	•
	•	•									

© November 2026 - All Rights Reserved