LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Dynamometer Tractel Dynafor™ Pro

Product information



This robust high-precision wireless digital dynamometer ensures a precision of 0,2%. It is resistant to shocks and weather, and therefor suitable for both indoor and outdoor use.

Specifications:

- Capacity range from 1t up to 250t
- Bluetooth chipset for a connection to any smartdevice equipped with free app, up to 30m
- Both Bluetooth and Radio-Frequency 2.4 GHz available
- Radio-Frequency 2.4GHz chipset for wireless range up to 400m with Tractel® Dynafor™ HHD, large displays AL63, DMU and software accessories
- 0.2% accuracy of full scale
- Powered by 3 AA batteries
- IP65

Options:

- Separate handheld display dynafor™ HHD, can reach a wireless range of 400 m
- High visibility display dynafor™ AL63, can reach a wireless range of 200 m
- IP67

... *Read more*


Material: Steel, aluminium
Marking: CE-mark, UKCA-marked
Temperature range: -20°C up to +50°C

© November 2026 - All Rights Reserved

LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Dynamometer Tractel Dynafor™ Pro

Blueprint



Technical data

Part code	Code	WLL (metric) tonnes	A in	B in	C in	D in	E in	G in	Weight lb
16.50293369	dynafor™ Pro 1t	1	8.5	7.59	0.85	3.11	0.91	1.54	1.54
16.50293379	dynafor™ Pro 3,2t	3.2	8.5	7.63	0.85	3.62	0.91	1.54	1.9
16.50293389	dynafor™ Pro 6,5t	6.5	9.76	8.43	1.13	4.45	1.26	1.54	3.53
16.50293399	dynafor™ Pro 15t	15	12.56	10.62	1.83	4.69	2.01	2.44	8.07
16.50293409	dynafor™ Pro 25t	25	14.06	11.88	2.26	5.2	2.4	2.56	11.75
16.50293419	dynafor™ Pro 50t	50	17.56	14.61	3.1	5.98	3.54	3.58	25.24
16.50293429	dynafor™ Pro 100t	100	22.01	17.88	4.24	7.72	5.08	5.26	60.58
16.50293439	dynafor™ Pro 250t	250	31.38	23.98	6.38	12.95	7.09	-	216.01

© November 2026 - All Rights Reserved