



Plate Clamp Tractel KT

Product information



Clamps for lifting and handling unit loads of steel (sheets, profiles, welded assemblies, steel structures, etc.).

Clamps fulfill the Machinery Directive 2006/42/EC.

... [Read more](#)

Marking: CE-marked


Temperature range: -20°C up to +100°C

Warning: The pieces can as well be taken from the side in order to tip them over. Never lift people with this equipment. Never use with a plate thickness thinner than the recommended minimum thickness or thicker than the recommended maximum thickness.



Plate Clamp Tractel KT

Blueprint



Technical data

| Part code | WLL (metric) tonnes | Jaw width in | A in | B in | C in | D in | Emin mm in | F in | Gmax mm in | H, in | Weight lb |
|-----------------|---------------------|--------------|------|------|------|------|------------|------|------------|-------|-----------|
| 502100050152830 | 0.5 | 0-0.59 | 1.18 | 1.69 | 1.34 | 0.59 | 4.17 | 0.39 | 8.5 | 1.97 | 4.41 |
| 502100100202830 | 1 | 0-0.79 | 1.89 | 2.48 | 1.97 | 0.79 | 5.71 | 0.47 | 11.5 | 2.6 | 9.92 |
| 502100200252830 | 2 | 0-0.98 | 2.68 | 3.07 | 2.4 | 0.98 | 6.85 | 0.63 | 14.53 | 2.99 | 16.09 |
| 502100300302830 | 3 | 0-1.18 | 2.91 | 3.35 | 2.24 | 1.18 | 8.15 | 0.79 | 16.85 | 4.02 | 33.07 |
| 502100500502830 | 5 | 0-1.97 | 3.15 | 3.94 | 2.6 | 1.97 | 9.45 | 0.94 | 18.94 | 4.33 | 47.62 |
| 502100800802830 | 8 | 1.77-3.15 | 3.15 | 5.51 | 3.19 | 3.15 | 12.91 | 0.94 | 22.01 | 4.69 | 84.44 |