



Lifting Plate Clamp Tractel TLH

Product information



Lifting of horizontal plates or sheets (individual or bundles), circular plates or fabricated assemblies.

Accessories equipped with a tip up lever ensuring the clamping of the load.

Use in pairs for lifting horizontal plates or sheet metals, individual or in bundles:

- 1 pair with a 2-legged sling
- Several pairs with 2-legged slings and lifting beam.
- Use in 3s with a 3-legged sling for lifting round sheet metals.

Fit the load into the clamps, making sure they are evenly distributed onto the piece to be lifted. Lifting ensures the clamps' locking. Clamping is proportional to the load lifted, thus avoiding an excessive marking.

Lifting Plate Clamp TLH fulfill the Machinery Directive 2006/42/EC.

... [Read more](#)

Marking: CE-marked

Temperature range: -20° up to +80°C

Finish: Hot epoxy coating


Note: To be used by pair!

Warning: Never lift people with this equipment !



Lifting Plate Clamp Tractel TLH

Blueprint



Technical data

Part code	Code	WLL (metric) tonnes	Jaw width in	Chain Ø mm	A in	B in	C in	D in	E in	F in	G, in	I mm in	J in	Weight lb
502100050601800	TLH1 0-60	0.5	0-2.36	6	6.1	1.57	0.47	3.15	3.54	0.47	0.39	0.79	3.15	6.61
502100051201800	TLH1 0-120	0.5	0-4.72	6	10.04	1.97	0.47	4.72	5.51	0.47	0.47	0.79	4.72	11.02
502100100601800	TLH2 0-60	1	0-2.36	8	6.5	2.09	0.79	3.94	4.69	0.55	0.47	0.79	3.94	11.02
502100101201800	TLH2 0-120	1	0-4.72	8	10.24	2.36	0.59	4.72	7.05	0.55	0.47	0.79	5.91	17.64
502100150601800	TLH3 0-60	1.5	0-2.36	10	7.17	2.36	0.79	3.94	4.92	0.63	0.47	0.79	3.94	13.23
502100151501800	TLH3 0-150	1.5	0-5.91	10	12.76	2.76	0.79	5.91	7.09	0.71	0.63	1.18	5.91	28.66
502100201201800	TLH4 0-60	2	0-2.36	10	7.56	2.72	0.98	4.33	4.92	0.87	0.63	0.79	3.94	17.64
502100201501800	TLH4 0-150	2	0-5.91	10	13.58	2.91	0.98	5.91	6.26	0.87	0.63	1.18	5.12	37.48
502100250601800	TLH5 0-60	2.5	0-2.36	13	7.76	2.95	0.98	4.72	5.91	0.87	0.63	0.79	5.12	22.05
502100251501800	TLH5 0-150	2.5	0-5.91	13	14.06	3.15	0.98	5.94	7.87	0.87	0.79	1.18	6.3	46.3
502100501501800	TLH10 0-150	5	0-5.91	16	14.49	3.94	1.18	6.3	9.45	1.38	0.94	1.18	7.09	35.27
502100500601800	TLH10 0-60	5	0-2.36	16	8.07	3.15	1.18	4.69	6.69	1.38	0.94	1.18	4.72	68.34