LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Lifting Plate Clamp Tractel TLH

Product information

Lifting of horizontal plates or sheets (individual or bundles), circular plates or fabricated assemblies.
Accessories equipped with a tip up lever ensuring the clamping of the load.

Use in pairs for lifting horizontal plates or sheet metals, individual or in bundles:

- 1 pair with a 2-legged sling
- Several pairs with 2-legged slings and lifting beam.
- Use in 3s with a 3-legged sling for lifting round sheet metals.

Fit the load into the clamps, making sure they are evenly distributed onto the piece to be lifted. Lifting ensures the clamps'
locking. Clamping is proportional to the load lifted, thus avoiding an excessive marking.

Lifting Plate Clamp TLH fulfill the Machinery Directive 2006/42/EC.

... *Read more*

Marking: CE-mark
Temperature range: -20° up to +80°C
Finish: Hot epoxy coating
Note: To be used by pair!
Warning: Never lift people with this equipment !

© November 2026 - All Rights Reserved

LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Lifting Plate Clamp Tractel TLH

Blueprint



Technical data

Code	WLL (metric) tonnes	Jaw width in	Chain Ø mm	A in	B in	C in	D in	E in	F in	G in	I in	J in	Weight lb
TLH1 0-60	0.5	0-2.36	6	6.1	1.57	0.47	3.15	3.54	0.47	0.39	0.79	3.15	6.61
TLH1 0-120	0.5	0-4.72	6	10.04	1.97	0.47	4.72	5.51	0.47	0.47	0.79	4.72	11.02
TLH2 0-60	1	0-2.36	8	6.5	2.09	0.79	3.94	4.69	0.55	0.47	0.79	3.94	11.02
TLH2 0-120	1	0-4.72	8	10.24	2.36	0.59	4.72	7.05	0.55	0.47	0.79	5.91	17.64
TLH3 0-60	1.5	0-2.36	10	7.17	2.36	0.79	3.94	4.92	0.63	0.47	0.79	3.94	13.23
TLH3 0-150	1.5	0-5.91	10	12.76	2.76	0.79	5.91	7.09	0.71	0.63	1.18	5.91	28.66
TLH4 0-60	2	0-2.36	10	7.56	2.72	0.98	4.33	4.92	0.87	0.63	0.79	3.94	17.64
TLH4 0-150	2	0-5.91	10	13.58	2.91	0.98	5.91	6.26	0.87	0.63	1.18	5.12	37.48
TLH5 0-60	2.5	0-2.36	13	7.76	2.95	0.98	4.72	5.91	0.87	0.63	0.79	5.12	22.05
TLH5 0-150	2.5	0-5.91	13	14.06	3.15	0.98	5.94	7.87	0.87	0.79	1.18	6.3	46.3
TLH10 0-150	5	0-5.91	16	14.49	3.94	1.18	6.3	9.45	1.38	0.94	1.18	7.09	35.27
TLH10 0-60	5	0-2.36	16	8.07	3.15	1.18	4.69	6.69	1.38	0.94	1.18	4.72	68.34

© November 2026 - All Rights Reserved