



## Automatic Lifting Clamp Tractel NK

### Product information



Clamps equipped with a spring safety system that ensures constant contact of the cam on the piece to be lifted, even when it is being set down. This model also features an automatic gripping system, ensuring the clamp closes when the sheet is positioned at the bottom of the throat. The non-protruding reset lever allows for use directly on the ground. The chain enables tilting and facilitates the placement of the clamp. The serrated cam only marks one side of the load.

Automatic Lifting Clamp NK fulfill the Machinery Directive 2006/42/EC.

... [Read more](#)

**Material:** Manufactured without load bearing welds

**Marking:** CE-marked

**Temperature range:** -20° up to +100°C


**Finish:** Hot epoxy coating

**Warning:** Never lift people with this equipment!



# Automatic Lifting Clamp Tractel NK

## Blueprint



## Technical data

Part code	Code	WLL (metric) tonnes	Jaw width in	A in	K in	B in	C in	D in	E in	F in	G, in	H, in	Imm in	J in	L in	Weight lb
502100150201850	NK1 0-20	1.5	0-0.79	17.13-18.5	7.28	4.72	1.18	0.31	2.68	3.25	4.33	0.31	2.36	0.41	3.23	8.82
502100150401850	NK1 20-40	1.5	0.79-1.57	17.64-19.41	8.82	5.94	1.73	0.31	3.19	3.25	4.33	0.31	2.36	0.41	3.82	13.23
502100150601850	NK1 40-60	1.5	1.57-2.36	18.23-20	9.84	6.73	1.73	0.31	3.78	3.25	3.94	0.31	2.36	0.41	4.41	13.23
502100300301850	NK2 0-30	3	0-1.18	23.39-25.39	10.94	7.48	2.28	0.51	3.74	4.8	4.61	0.87	2.68	0.81	4.72	28.66
502100300601850	NK2 30-60	3	1.18-2.36	23.94-26.06	12.2	8.27	2.56	0.51	4.45	4.8	4.61	0.87	2.68	0.81	5.59	33.07
502100300901850	NK2 60-90	3	2.36-3.54	24.84-26.77	13.31	9.65	2.76	0.51	5.04	4.8	4.61	0.87	2.68	0.81	6.18	37.48
502100450401850	NK3 0-40	4.5	0-1.57	25.39-27.99	14.25	9.84	2.6	0.51	5.31	5.51	4.61	0.87	2.68	0.81	6.42	55.12
502100450801850	NK3 40-80	4.5	1.57-3.15	25.79-28.31	15.55	10.63	3.15	0.51	6.3	5.91	4.61	0.87	2.68	0.81	7.4	57.32
502100451201850	NK3 80-120	4.5	3.15-4.72	27.4-29.92	14.61	12.28	3.23	0.51	7.09	5.71	4.53	0.87	2.6	0.81	8.19	59.52
502100750501850	NK5 0-50	7.5	0-1.97	39.09-43.62	15.83	12.83	3.86	0.71	5.91	9.25	8.07	1.38	3.94	0.98	7.87	92.59
502100751001850	NK5 50-100	7.5	1.97-3.94	41.26-45.75	17.68	12.99	3.74	0.71	8.07	9.25	8.07	1.38	3.94	0.98	9.61	110.23
502100751501850	NK5 100-150	7.5	3.94-5.91	42.52-46.77	18.66	15.55	4.13	0.71	9.06	9.25	8.07	1.38	3.94	0.98	10.51	132.28