LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Automatic Lifting Clamp Tractel NK

Product information



Clamps equipped with a spring safety system that ensures constant contact of the cam on the piece to be lifted, even when it is being set down. This model also features an automatic gripping system, ensuring the clamp closes when the sheet is positioned at the bottom of the throat. The non-protruding reset lever allows for use directly on the ground. The chain enables tilting and facilitates the placement of the clamp. The serrated cam only marks one side of the load.

Automatic Lifting Clamp NK fulfill the Machinery Directive 2006/42/EC.

... *Read more*


Material: Manufactured without load bearing welds
Marking: CE-mark
Temperature range: -20° up to +100°C
Finish: Hot epoxy coating
Warning: Never lift peole with this equipment!

© November 2026 - All Rights Reserved

LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Automatic Lifting Clamp Tractel NK

Blueprint



Technical data

Code	WLL (metric) tonnes	Jaw width in	A in	K in	B in	C in	D in	E in	F in	G in	H in	I in	J in	L in	Weight lb
NK1 0-20	1.5	0-0.79	17.13-18.5	7.28	4.72	1.18	0.31	2.68	3.25	4.33	0.31	2.36	0.41	3.23	8.82
NK1 20-40	1.5	0.79-1.57	17.64-19.41	8.82	5.94	1.73	0.31	3.19	3.25	4.33	0.31	2.36	0.41	3.82	13.23
NK1 40-60	1.5	1.57-2.36	18.23-20	9.84	6.73	1.73	0.31	3.78	3.25	3.94	0.31	2.36	0.41	4.41	13.23
NK2 0-30	3	0-1.18	23.39-25.39	10.94	7.48	2.28	0.51	3.74	4.8	4.61	0.87	2.68	0.81	4.72	28.66
NK2 30-60	3	1.18-2.36	23.94-26.06	12.2	8.27	2.56	0.51	4.45	4.8	4.61	0.87	2.68	0.81	5.59	33.07
NK2 60-90	3	2.36-3.54	24.84-26.77	13.31	9.65	2.76	0.51	5.04	4.8	4.61	0.87	2.68	0.81	6.18	37.48
NK3 0-40	4.5	0-1.57	25.39-27.99	14.25	9.84	2.6	0.51	5.31	5.51	4.61	0.87	2.68	0.81	6.42	55.12
NK3 40-80	4.5	1.57-3.15	25.79-28.31	15.55	10.63	3.15	0.51	6.3	5.91	4.61	0.87	2.68	0.81	7.4	57.32
NK3 80-120	4.5	3.15-4.72	27.4-29.92	14.61	12.28	3.23	0.51	7.09	5.71	4.53	0.87	2.6	0.81	8.19	59.52
NK5 0-50	7.5	0-1.97	39.09-43.62	15.83	12.83	3.86	0.71	5.91	9.25	8.07	1.38	3.94	0.98	7.87	92.59
NK5 50-100	7.5	1.97-3.94	41.26-45.75	17.68	12.99	3.74	0.71	8.07	9.25	8.07	1.38	3.94	0.98	9.61	110.23
NK5 100-150	7.5	3.94-5.91	42.52-46.77	18.66	15.55	4.13	0.71	9.06	9.25	8.07	1.38	3.94	0.98	10.51	132.28

© November 2026 - All Rights Reserved