



Automatic Lifting Clamp Tractel NX-NXR

Product information



Lifting and tilting of smooth or polished pieces such as stainless steel plates, aluminum, pre-coated materials, wood, laminated materials, marble, concrete, glass, plastic. Clamps equipped with polyurethane-covered jaws allow lifting and tilting loads without marking their surface. These products feature a spring safety system and an automatic gripping mechanism, ensuring constant contact of the cam on the piece to be lifted, even when it is being set down, and ensuring the clamp closes when the sheet is positioned at the bottom of the throat. A handle facilitates gripping. The chain enables tilting and facilitates the placement of the clamp.

Automatic Lifting Clamp NX-NXR fulfill the Machinery Directive 2006/42/EC. [... Read more](#)

Material: Manufactured without load bearing welds

Marking: CE-marked

Temperature range: -20° up to +80°C


Finish: Hot epoxy coating

Warning: Never lift people with this equipment !



Automatic Lifting Clamp Tractel NX-NXR

Blueprint



Technical data

Part code	Code	WLL (metric) tonnes	Jaw width in	Chain Ø mm	A in	B in	C in	D in	E in	F in	G, in	H, in	I mm in	J in	K in	L in	M mm in	O mm in	P mm in	Weight lb
502100050201910	NX05 0-20	0.5	0-0.79	7	6.73-8.7	8.19	3.23	1.97	4.13	14.8- 18.11	1.65	2.8	1.61	0.51	0.43	3.15	2.76	X	4.65	9.92
502100051201910	NXR05 20- 120	0.5	0.79-4.72	7	7.99- 12.87	8.19	3.23	2.28	4.13	14.96- 17.56	2.28	2.8	1.61	0.51	0.43	3.15	2.76	0.79	4.65	12.74
502100051001910	NXR05 0- 100	0.5	0-3.94	7	7.01- 12.13	8.19	3.23	2.28	4.13	14.92- 18.35	2.28	2.8	1.61	0.51	0.43	3.15	2.76	0.79	4.65	13.23
502100051401910	NXR05 40- 140	0.5	1.57-5.51	7	8.78- 13.7	8.19	3.23	2.28	4.13	15.04- 18.07	2.28	2.8	1.61	0.51	0.43	3.15	2.76	0.79	4.65	13.23
502100150301910	NX1.5 0-30	1.5	0-1.18	10	8.66- 11.22	10.08	4.09	2.68	4.72	20-24.02	2.2	3.43	1.93	0.51	0.63	3.94	3.54	X	5.71	24.25