



Swivel Jaw / Hook Crosby S1

Product information



Design: Swivel with jaw and hook equipped with tapered roller thrust bearing.

Features:

- Suitable for frequent rotation under load.
- All swivels individually Proof Tested to 2 times the Working Load Limit.
- Pressure lube fitting provided
- All hooks furnished with latches
- All jaws complete with bolts, nuts and cotter pins.
- Other types and capacities up to 1250t available on demand.

... [Read more](#)

Marking: CE-marked

Note: Always check before use if your steel wire rope is suitable for use with a swivel.


Warning: Not to be used on demolition- (wrecking-) balls!

Safety factor: 5:1



Swivel Jaw / Hook Crosby S1

Blueprint



Technical data

Part code	Rope Ø range mm	WLL (metric) tonnes	Swivel No	A in	F in	G, in	H, in	J in	K in	L in	Mmm in	Nmm in	Omm in	Pmm in	V mm in	Weight lb
11.46297011	13	3	3-S-1	11.46	4.84	2.76	0.75	0.88	1.62	1.53	1.41	1.31	1	1.44	1.12	9.81
11.46297217	16	5	5-S-1	13.35	6.3	2.99	0.88	1	2.24	1.94	1.69	1.62	1.12	1.81	1.44	15.52
11.46297413	19	8.5	8-S-1	16.46	7.56	4.02	1	1.56	2.81	2.46	2.22	2.13	1.38	2.24	1.62	29.32
11.46297618	22	10	10-S-1	19.76	8.35	4.49	1.5	1.75	3.39	2.6	2.4	3.5	1.75	2.6	1.94	46.74
11.46297814	26	15	15-S-1	22.24	10.35	5	1.5	1.75	3.39	2.81	3.19	3.5	1.75	2.99	2.38	73.85
11.46298118		25	25-S-1	26.77	13.62	5.98	2.01	2.01	4.61	3.44	3.62	3.68	2.38	3.66	2.99	141.1
11.46298216		35	35-S-1	29.92	14.06	6.5	2.01	2.01	4.61	3.88	3.76	3.68	2.38	4.57	3.19	220.46
11.46298314		45	45-S-1	35.08	15.43	7.01	2.24	2.5	5	4.76	4.25	4.02	2.99	5.08	3.25	251.33