



Swivel Eye / Eye Crosby S5

Product information



Design: Swivel with eyes equipped with tapered roller thrust bearing.

Features:

- Suitable for frequent rotation under load.
- All swivels individually Proof Tested to 2 times the Working Load Limit.
- Pressure lube fitting provided
- Other types and capacities up to 1250 t available on demand.

... [Read more](#)

Marking: CE-marked

Note: Always check before use if your steel wire rope is suitable for use with a swivel.


Warning: Not to be used on demolition- (wrecking-) balls!

Safety factor: 5:1



Swivel Eye / Eye Crosby S5

Blueprint



Technical data

Part code	WLL (metric) tonnes	Rope Ø mm	Swivel No	D in	G, in	Qmm in	Rmm in	S in	T in	Weight lb
11.46297057	3	13	3-S-5	9.41	2.76	0.75	1.03	1.12	1.25	8.51
11.46297253	5	16	5-S-5	9.8	2.99	1	1.28	1.25	1.25	11.31
11.46297459	8.5	19	8-S-5	11.89	4.02	1.25	1.41	1.62	1.5	29.32
11.46297654	10	22	10-S-5	15.51	4.49	1.69	1.69	2.76	1.88	42.11
11.46297850	15	26	15-S-5	16.38	5	1.94	2.03	2.76	2.13	48.94
11.46298154	25	-	25-S-5	22.24	5.98	2.24	2.3	3.88	2.38	130.07
11.46298252	35	-	35-S-5	22.24	6.5	2.24	2.3	3.88	2.38	145.51
11.46298350	45	-	45-S-5	26.5	7.01	2.5	2.54	4.02	2.99	216.05