



## Screw Pin Chain Shackle Crosby G-210

### Product information



**Design:** Screw pin anchor shackles meet the performance requirements of Federal Specification RR-C-271G Type IVA, Grade A, Class 2, except for those provisions required of the contractor.

... [Read more](#)

**Material:** Forged - Quenched and Tempered, with alloy pins.

**Marking:** According to standard, CE-marked

**Temperature range:** -40° C to 204° C

**Finish:** Hot Dip galvanized or self colored.

**Standard:** US. FED. SPEC. RR-C-271F, ASME B30.26


**Safety factor:** 6:1

**Grade:** 6



## Screw Pin Chain Shackle Crosby G-210

### Blueprint



### Technical data

Part code	WLL (metric) tonnes	Size inch	A in	B in	C in	D in	F in	G in	H in	L in	M in	P in	Weight lb
11.311019150	0.5	1/4	0.47	0.31	0.87	0.24	0.63	0.98	1.57	0.2	1.42	0.24	0.11
11.311019178	0.75	5/16	0.55	0.39	1.02	0.31	0.75	1.14	1.89	0.24	1.69	0.31	0.18
11.311019196	1	3/8	0.67	0.43	1.26	0.39	0.91	1.42	2.32	0.24	2.05	0.39	0.29
11.311019212	1.5	7/16	0.75	0.51	1.46	0.43	1.06	1.61	2.68	0.31	2.36	0.43	0.44
11.311019230	2	1/2	0.83	0.63	1.61	0.51	1.18	1.81	3.03	0.39	2.68	0.51	0.6
11.311019258	3.25	5/8	1.06	0.75	2.01	0.63	1.5	2.32	3.78	0.43	3.35	0.63	1.26
11.311019276	4.75	3/4	1.26	0.87	2.36	0.75	1.81	2.76	4.53	0.51	3.98	0.83	2.27
11.311019294	6.5	7/8	1.46	0.98	2.8	0.87	2.09	3.19	5.31	0.51	4.49	0.98	3.15
11.311019310	8.5	1	1.69	1.14	3.19	0.98	2.36	3.7	5.94	0.55	5.12	0.98	4.74
11.311019338	9.5	11/8	1.81	1.26	3.54	1.14	2.68	4.06	6.77	0.63	5.98	1.26	6.75
11.311019356	12	11/4	2.05	1.42	3.94	1.26	2.99	4.53	7.52	0.71	6.5	1.38	9.06
11.311019374	13.5	13/8	2.24	1.57	4.37	1.38	3.31	5	8.27	0.75	6.93	1.5	11.64
11.311019392	17	11/2	2.36	1.65	4.88	1.5	3.62	5.39	9.06	0.83	7.44	1.61	15.94
11.311019418	25	13/4	2.87	2.05	5.75	1.73	4.17	6.38	10.98	0.98	9.17	2.13	26.68
11.311019436	35	2	3.27	2.28	6.73	2.09	5	7.24	12.76	1.14	10.35	2.36	42.33
11.311019454	55	21/2	4.13	2.8	7.99	2.64	5.67	9.37	14.84	1.38	13.19	2.64	71.65