LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Bolt Type Anchor Shackle Crosby G-2130

Product information



Bolt Type Anchor shackles with thin head bolt - nut with cotter pin. Meets the performance requirements of Federal Specification RR-C 271G Type IVA, Grade A, Class 3, except for those provisions required of the contractor.
Proof load: 2 x WLL.

... *Read more*

Material: Forged – Quenched and Tempered, with alloy bolts
Marking: According to standard, CE-mark, WLL, RFID chip for 25T and higher.
Temperature range: -40°C up to +204°C
Finish: Galvanized with painted bolt.
Standard: ASME B30.26, US. FED. SPEC. RR-C-271, ISO 2415

Safety factor: 6:1
Grade: 6

© November 2026 - All Rights Reserved

LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Bolt Type Anchor Shackle Crosby G-2130

Blueprint



Technical data

Part code	WLL (metric) tonnes	Size inch	A in	B in	C in	D in	E in	F in	H in	L in	M in	N in	A Tolerance +/- in	C Tolerance +/- in	Weight lb
11.311019464	0.33	3/16	0.35	0.24	0.87	0.16	0.59	0.55	1.46	0.94	1.26	0.16	0.04	-	0.07
11.311019466	0.5	1/4	0.43	0.28	1.1	0.24	0.75	0.59	1.81	1.26	1.54	0.24	0.04	0.04	0.11
11.311019468	0.75	5/16	0.51	0.35	1.22	0.28	0.83	0.75	2.09	1.46	1.81	0.28	0.04	0.04	0.22
11.311019470	1	3/8	0.63	0.43	1.42	0.35	1.02	0.91	2.48	1.77	2.17	0.35	0.04	0.04	0.33
11.311019471	1.5	7/16	0.75	0.47	1.65	0.43	1.14	1.02	2.91	2.01	2.48	0.43	0.04	0.12	0.49
11.311019472	2	1/2	0.79	0.63	1.85	0.47	1.3	1.18	3.27	2.28	2.8	0.47	0.04	0.12	0.79
11.311019490	3.25	5/8	1.02	0.75	2.36	0.63	1.65	1.5	4.17	2.91	3.54	0.67	0.04	0.12	1.68
11.311019515	4.75	3/4	1.22	0.87	2.8	0.75	2.01	1.81	4.96	3.5	4.13	0.79	0.04	0.24	2.71
11.311019533	6.5	7/8	1.42	0.98	3.31	0.87	2.28	2.09	5.83	4.02	4.8	0.94	0.04	0.24	3.95
11.311019551	8.5	1	1.65	1.1	3.74	0.98	2.68	2.36	6.57	4.69	5.39	1.02	0.04	0.24	5.67
11.311019579	9.5	1-1/8	1.81	1.22	4.25	1.1	2.91	2.68	7.48	5.16	5.91	1.22	0.04	0.24	8.27
11.311019597	12	1-1/4	2.01	1.38	4.69	1.22	3.23	2.99	8.27	5.75	6.69	1.38	0.04	0.24	11.71
11.311019613	13.5	1-3/8	2.24	1.5	5.24	1.38	3.62	3.31	9.17	6.38	7.2	1.5	0.12	0.24	15.83
11.311019631	17	1-1/2	2.36	1.61	5.75	1.5	3.86	3.62	10	6.89	7.72	1.61	0.12	0.24	19
11.311019659	25	1-3/4	2.87	2.01	7.01	1.73	5	4.17	12.32	8.86	9.69	2.24	0.12	0.24	33.95
11.311019677	35	2	3.23	2.24	7.76	2.01	5.75	4.8	13.7	9.96	10.83	2.4	0.12	0.24	52.25
11.311019695	55	2-1/2	4.13	2.76	10.51	2.6	7.24	5.71	17.83	12.87	13.58	3.11	0.24	0.24	98.33
11.311019711	85	3	5	3.23	12.99	2.99	7.87	6.5	21.5	14.37	15.12	3.62	0.24	0.24	154.1
11.311019739	120	3-1/2	5.24	3.74	14.65	3.62	9.02	7.99	24.65	16.5	17.01	4.13	0.24	0.24	264.55
11.311019757	150	4	5.51	4.25	14.49	4.09	10	9.02	25.71	18.43	17.76	4.57	0.24	0.24	337.31

© November 2026 - All Rights Reserved