LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Bolt Type Chain Shackle Crosby G-2150

Product information

Design: Bolt Type Chain shackle. Thin hex head boltnut with cotter pin.

Meets the performance requirements of Federal Specification RR-C-271H, Type IVB, Grade A, Class 3, except for those provisions required of the contractor.
... *Read more*

Material: Forged — Quenched and Tempered, with alloy pins.
Marking: According to standard, CE-mark
Finish: Hot Dip galvanized or self colored.
Standard: EN 13889, US. FED. SPEC. RR-C-271, ASME B30.26

Safety factor: 6:1
Grade: 6

© November 2026 - All Rights Reserved

LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Bolt Type Chain Shackle Crosby G-2150

Blueprint



Technical data

Part code	WLL (metric) tonnes	A in	B in	D in	F in	G in	K in	M in	P in	R in	A Tolerance +/- in	G Tolerance +/- in	Weight lb
11.301019768	0.5	0.47	0.31	0.25	0.61	0.75	1.59	0.97	1.56	0.25	0.06	0.06	0.13
11.301019770	0.75	0.53	0.38	0.31	0.75	1	1.91	1.16	1.82	0.31	0.06	0.06	0.22
11.301019772	1	0.66	0.44	0.38	0.91	1.22	2.3	1.41	2.17	0.38	0.06	0.13	0.33
11.301019774	1.5	0.75	0.5	0.44	1.06	1.42	2.66	1.63	2.5	0.44	0.06	0.13	0.49
11.301019775	2	0.81	0.63	0.5	1.19	1.63	3.03	1.81	2.8	0.5	0.06	0.13	0.75
11.301019793	3.25	1.06	0.75	0.63	1.5	2.01	3.76	2.3	3.52	0.63	0.06	0.13	1.48
11.301019819	4.75	1.25	0.88	0.75	1.81	2.38	4.53	2.76	4.06	0.81	0.06	0.25	2.51
11.301019837	6.5	1.44	1	0.88	2.09	2.81	5.31	3.19	4.72	0.97	0.06	0.25	3.86
11.301019855	8.5	1.69	1.13	1	2.38	3.19	5.94	3.68	5.31	1	0.06	0.25	5.56
11.301019873	9.5	1.81	1.25	1.13	2.7	3.58	6.77	4.06	5.91	1.25	0.06	0.25	7.61
11.301019891	12	2.03	1.38	1.25	2.99	3.94	7.52	4.53	6.5	1.38	0.06	0.25	10.8
11.301019917	13.5	2.24	1.5	1.38	3.31	4.37	8.27	5	7.2	1.5	0.13	0.25	13.76
11.301019935	17	2.38	1.63	1.5	3.62	4.8	9.06	5.39	7.72	1.62	0.13	0.25	17.02
11.301019953	25	2.87	2.01	1.75	4.17	5.75	10.98	6.38	9.06	2.13	0.13	0.25	31.31
11.301019971	35	3.25	2.24	2.01	4.8	6.77	12.28	7.24	10.39	2.36	0.13	0.25	46.74
11.301019991	55	4.13	2.76	2.62	5.71	7.99	14.84	9.37	13.54	2.62	0.25	0.25	85.1
11.301020013	85	5	3.25	2.99	6.5	8.5	16.89	10.98	16.5	3.5	0.25	0.25	124.34

© November 2026 - All Rights Reserved