



## Swivel Hook Crosby S-1326

### Product information



The S-1326 hook is a positioning device and is not intended to rotate under load.

#### Features:

- Individually Proof Tested at 2-1/2 times the 4:1 Working Load Limit with certification.
- Recessed trigger design is flush with the hook body, protecting the trigger from potential damage.
- Easy to operate with enlarged thumb access.
- Positive Lock Latch is Self-Locking when hook is loaded.
- Rated for both Wire Rope and use with Grade 80/100 Chain.

... [Read more](#)

**Material:** Forged Alloy Steel - Quenched and Tempered.

**Finish:** Painted


**Safety factor:** 4:1

**Grade:** 10



## Swivel Hook Crosby S-1326

### Blueprint



### Technical data

Part code	Chain diameter	WLL (metric) tonnes	A in	B in	C in	D in	E in	F in	H in	J in	L in	AA**mm in	Weight lb
11.161004304	6	1.45	1.5	1.32	6.14	0.79	2.6	0.67	0.5	0.63	1.13	1.5	1.26
11.161004313	7-8	2.6	1.75	1.59	7.6	1.1	3.5	0.87	0.63	0.81	1.38	2.01	2.6
11.161004322	10	4	2	1.73	8.82	1.17	4.41	1.1	0.75	0.94	1.75	2.5	4.7
11.161004331	13	6.8	2.5	2.38	11.18	1.67	5.47	1.26	1	1.16	2.11	3	8.64
11.161004340	16	10.3	2.75	2.53	12.91	2.04	6.57	1.5	1.13	1.5	2.49	3.5	17
11.161004349	18-20	16	2.83	2.52	14.09	2.22	7.76	2.01	1.1	2.03	3.52	5	24.03
11.161004358	22	20	3.44	3.19	16.42	2.45	8.74	2.26	1.3	2.2	3.83	5.98	29.1