



LAM-É
ST-PIERRE

Lifting Solutions Group
Axel Johnson International



Clevis Hook Crosby S-1317

Product information

- 25% stronger than Grade 80
- Individually Proof tested to 2-1/2 times the Working Load Limit with certification.
- Recessed trigger design is flush with the hook body, protecting the trigger from potential damage.
- Easy to operate with enlarged thumb access.
- Positive Lock Latch is Self-Locking when hook is loaded.
- Suitable for use with Grade 100 and Grade 80 chain.

Material: Forged alloy steel - Quenched and Tempered.

Warning: Not heat-treated

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL (metric) tonnes	EWL mm	C mm	D mm	E mm	G mm	J mm	L	AA mm	Weight kg
402300150090	6	1.5	87	87.4	20.1	66	121	16	29	38.1	0.35
402300200090	7	2	114	114	27.9	89	159	20.6	35.1	51	0.82
402300260090	8	2.6	114	114	27.9	89	159	20.6	35.1	51	0.82
402300400090	10	4	140	140	29.7	112	192	24.1	46.5	63.5	1.66
402300680090	13	6.8	173	173	42.4	139	242	29.5	56.4	76.2	3.08
402301030090	16	10.3	209	209	51.8	167	295	38.1	67.3	89	5.4
402301600090	18-20	16	239	239	56.4	197	336	51.6	89.4	-	6.8
402302000090	22	20	283	283	62.2	222	392	55.9	97.3	-	12.7
402302710090	26	27.1	319	319	81.5	251	468	68.1	104	-	22.5

Blueprint

