



## Eye Foundry Hook Crosby A-1329

### Product information



#### Features:

- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification.
- Suitable for use with Grade 100 and Grade 80 chain.
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.
- Hook can be tip loaded at the reduced Working Load Limit. Operator must ensure the load is retained properly in the hook

... [Read more](#)

**Material:** Forged Alloy steel - Quenched and Tempered.

**Warning:** Not to be heat-treated.


**Safety factor:** 4:1

**Grade:** 10



## Eye Foundry Hook Crosby A-1329

### Blueprint



### Technical data

Part code	Chain diameter mm	WLL (metric) tonnes	WLL Tip of the Hook ton	B in	D in	I in	K in	L in	M in	N in	O in	Weight lb
11.161026280	7-8	2.6	1.3	1.56	4.82	0.88	1.57	0.63	4.81	2.5	1.13	2.01
11.161026289	10	4	2	2.07	5.82	1.3	1.88	0.81	5.5	3	1.38	3.79
11.161026297	13	6.8	3.4	2.53	7.04	1.5	2.25	1.03	7.11	3.5	1.63	7.21
11.161026306	16	10.3	5.1	3	8.17	1.75	2.53	1.25	7.96	4	2.19	12.3
11.161026315	18-20	16	8	4.13	9.65	2.2	3.39	1.97	10.75	5	2.4	22.93
11.161026324	22-23	21	10	4.77	11.03	2.72	3.74	2.28	12.25	5.5	3.07	40.57
11.161026333	26	27.1	13.5	5.33	11.9	2.83	3.93	2.56	13.37	6	3.31	51.81
11.161026342	32	41	20.5	6.61	13.25	3.5	4.33	3.15	15.25	6.5	3.84	84.44