



Eye Foundry Hook Crosby A-1329

Product information

Features:

- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification.
- Suitable for use with Grade 100 and Grade 80 chain.
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.
- Hook can be tip loaded at the reduced Working Load Limit. Operator must ensure the load is retained properly in the hook

Material: Forged Alloy steel - Quenched and Tempered.

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL (metric) tonnes	WLL Tip of the Hook ton	B mm	D mm	I mm	K mm	L	M mm	N mm	O mm	Weight kg
11.161026280	7-8	2.6	1.3	39.6	122.4	22.4	39.9	16	122.2	63.5	28.7	0.91
11.161026289	10	4	2	52.6	147.8	33	47.8	20.6	139.7	76.2	35.1	1.72
11.161026297	13	6.8	3.4	64.3	178.8	38.1	57.2	26.2	180.6	88.9	41.4	3.27
11.161026306	16	10.3	5.1	76.2	207.5	44.5	64.3	31.8	202.2	101.6	55.6	5.58
11.161026315	18-20	16	8	104.9	245.1	55.9	86.1	50	273.1	127	61	10.4
11.161026324	22-23	21	10	121.2	280.2	69.1	95	57.9	311.2	139.7	78	18.4
11.161026333	26	27.1	13.5	135.4	302.3	71.9	99.8	65	339.6	152.4	84.1	23.5
11.161026342	32	41	20.5	167.9	336.6	88.9	110	80	387.4	165.1	97.5	38.3

Blueprint

