



Welded Master Link Crosby A-1343

Product information



Features:

- Ratings below are for use with chain slings fabricated in accordance with ASTM B30.9.
- Individually Proof Tested to values shown.
- Meets or exceeds all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, this master link meets other critical performance requirements including fatigue life, impact properties and material traceability, not addressed by ASME B30.26 ... [Read more](#)

Material: Alloy Steel - Quenched and Tempered.

Marking: According to standard, CE-marked, Code and grade

Finish: Painted

Standard: EN 1677-4


Safety factor: 5:1

Grade: 10



Welded Master Link Crosby A-1343

Blueprint



Technical data

Part code	WLL (metric) tonnes	A in	B in	C in	Weight lb
-	3.2	0.51	2.36	4.72	0.88
11.021247087	4.1	0.67	3.54	6.3	1.85
11.021247096	6.7	0.75	3.54	6.3	2.43
-	7	0.87	5.71	10.83	5.07
-	8.8	0.87	3.94	7.09	3.53
-	8.9	0.98	5.71	10.83	6.61
11.021247124	11.5	0.98	4.53	8.27	5.29
11.021247133	13	1.1	5.71	10.83	8.6
11.021247142	17	1.26	5.71	10.83	10.58
11.021247151	24	1.42	6.1	11.22	15.21
11.021247160	31.5	1.57	5.51	10.63	16.09
-	38.3	1.77	7.09	13.39	28.44
11.021247165	45	2.01	8.46	15.35	42.11
-	67	2.17	7.99	15.98	55.34



Welded Master Link Crosby A-1343

Part code	Grade 100 Chain, 1- leg mm	Grade 100 Chain, 2- leg mm	Grade 80 Chain, 1-leg mm	Grade 80 Chain, 2-leg mm
402100320050	6-7	6-7	6-8	6-8
402100410050	8-10	8	8-10	8
402100670050	10-13	10	10-13	10
402100700050	10-13	10	10-13	10
402100880050	13	10	13-16	13
402100890050	13	-	13-16	13
402101150050	13-16	13	16	16
402101300050	13-16	13	16	16
402101700050	16	16	19-20	19-20
402102400050	20	20	20-22	20-22
402103150050	22-23	22-23	23-26	23-26
402103830050	26	26	26	26
402104500051	26	26	32	32
402106700050	32	32	32	32