



Welded Master Link Assembly Crosby A-1346

Product information



Features:

- Ratings below are for use with chain slings fabricated in accordance with ASTM B30.9.
- Individually Proof Tested to values shown.
- Meets or exceed all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, this master link meet other critical performance requirements including fatigue life, impact properties and material traceability, not addressed by ASME B30.26 ... [Read more](#)


Material: Alloy Steel - Quenched and Tempered.
Marking: According to standard, Code and grade
Finish: Painted
Standard: EN 1677-4

Safety factor: 5:1
Grade: 10



Welded Master Link Assembly Crosby A-1346

Blueprint



Technical data

Part code	Chain diameter mm	WLL (metric) tonnes	A in	B in	C in	D in	E in	F in	Weight lb
-	6	3.2	0.51	2.36	4.72	0.51	2.36	4.72	2.43
11.021256868	6	4.1	0.67	3.54	6.3	0.51	2.36	4.72	3.53
11.021256874	7	4.2	0.75	3.54	6.3	0.51	2.36	4.72	3.97
-	8	7	0.87	3.94	7.09	0.67	3.54	6.3	7.28
-	8	7	0.87	5.71	10.83	0.67	3.54	6.3	9.04
-	10	8.5	0.87	3.94	7.09	0.75	3.54	6.3	8.38
-	10	8.9	0.98	4.53	8.27	0.75	3.54	6.3	10.14
11.021256892	10	8.9	0.98	5.71	10.83	0.75	3.54	6.3	11.46
11.021256917	13	14.5	1.1	5.71	10.83	0.87	3.94	7.09	15.65
11.021256926	13	17	1.26	5.71	10.83	0.98	4.53	8.27	21.16
11.021256935	16	23.6	1.42	6.1	11.22	1.1	4.33	7.48	28
-	16	28.1	1.57	5.51	10.63	1.26	5.71	10.83	40.57
11.021256953	19-20	38.3	1.77	7.09	13.39	1.42	6.1	11.22	58.64
-	22-23	45	2.01	8.46	15.35	1.57	5.51	10.63	78.26
-	26	67	2.17	7.99	15.98	2.01	8.46	15.35	134.7