



Eye / Eye Crosby HG-226

Product information



End fittings are quenched and tempered, bodies heat treated by normalizing. Turnbuckle eyes are forged elongated, by design, to maximize easy attachment in system and minimize stress in the eye. For turnbuckle sizes 6 mm through 64 mm, a shackle one size smaller can be reeved through eye.

Standard: According to Federal Specifications FF-T-791b.

... [Read more](#)

Marking: Logo, size and type.

Finish: Hot dipped galvanized.


Note: Turnbuckles recommended for straight or in-line pull only.

Safety factor: 5:1



Eye / Eye Crosby HG-226

Blueprint





Eye / Eye Crosby HG-226

Technical data

Part code	WLL lb	Thread dia. & take up inch	A in	J open in	K closed in	M open in	N closed in	R in	S in	X closed in	BB in	Weight lb
11.511031270	800	5/16 x 4-1/2	0.31	13.94	9.41	14.49	9.96	0.95	0.44	2.2	4.57	0.49
11.511031298	1,200	3/8 x 6	0.38	17.56	11.57	18.23	12.24	1.13	0.53	2.48	6.1	0.75
11.511031314	2,200	1/2 x 6	0.5	19.92	13.94	20.83	14.8	1.41	0.71	3.56	6.02	1.72
11.511031350	2,200	1/2 x 12	0.5	32.24	20.24	33.11	21.1	1.41	0.71	3.54	12.36	2.62
11.511031378	3,500	5/8 x 6	0.63	21.73	15.71	22.72	16.73	1.8	0.88	4.33	6.02	2.76
11.511031412	3,500	5/8 x 12	0.63	34.06	22.05	35.08	23.07	1.8	0.88	4.33	12.4	4.12
11.511031430	5,200	3/4 x 6	0.75	23.23	17.24	24.49	18.5	2.09	1	5.12	6.14	4.21
11.511031476	5,200	3/4 x 12	0.75	35.63	23.62	36.89	24.88	2.09	1	5.08	12.6	6.13
11.511031494	5,200	3/4 x 18	0.75	47.64	29.65	48.9	30.91	2.09	1	5.12	18.54	7.83
11.511031519	7,200	7/8 x 12	0.87	36.69	24.69	38.19	26.18	2.38	1.25	5.79	12.17	8.84
11.511031537	7,200	7/8 x 18	0.87	49.17	31.18	50.67	32.68	2.38	1.25	5.79	18.62	11.51
11.511031555	10,000	1 x 6	1	26.22	20.24	27.99	22.01	3	1.43	6.5	6.18	9.61
11.511031573	10,000	1 x 12	1	38.23	26.22	40	27.99	3	1.43	6.5	12.17	12.96
11.511031591	10,000	1 x 18	1	50.24	32.24	52.01	34.02	3	1.43	6.5	18.19	16.31
11.511031617	10,000	1 x 24	1	62.83	38.86	64.61	40.59	3	1.43	6.06	24.84	20.15
11.511031635	15,200	1-1/4 x 12	1.25	42.13	30.16	44.37	32.36	3.59	1.82	8.5	12.05	19.86
11.511031653	15,200	1-1/4 x 18	1.25	54.13	36.14	56.38	38.39	3.63	1.82	8.5	18.07	23.81
11.511031671	15,200	1-1/4 x 24	1.25	66.69	42.72	68.94	44.92	3.59	1.82	8.5	24.61	27.78
11.511031699	21,400	1-1/2 x 12	1.5	44.25	32.24	46.73	34.72	4.09	2.12	9.45	12.32	28.66
11.511031715	21,400	1-1/2 x 18	1.5	56.22	38.23	58.74	40.75	4.09	2.12	9.45	18.31	33.95
11.511031733	21,400	1-1/2 x 24	1.5	68.86	44.84	71.38	47.36	4.09	2.12	9.45	24.92	39.46
11.511031779	28,000	1-3/4 x 18	1.75	57.36	39.37	60.39	42.36	4.65	2.38	9.96	18.39	50.71
11.511031797	28,000	1-3/4 x 24	1.75	69.37	45.39	72.36	48.39	4.65	2.38	9.96	24.37	58.2
11.511031813	37,000	2 x 24	2	75.67	51.69	79.17	55.2	5.83	2.69	13.03	24.49	83.56
11.511031831	60,000	2-1/2 x 24	2.5	79.17	55.2	83.19	59.17	6.5	3.12	13.78	24.61	148.59
11.511031859	75,000	2-3/4 x 24	2.75	81.34	57.32	85.83	61.85	7.01	3.25	15.08	24.65	174.39