LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Crane Scale Radiolink Plus Crosby

Product information



Crane scale for both weighing and dynamic load monitoring.
Shackle: Crosby G2130.
Battery type/life: Handheld 2 x AA/Load cell 4 x AA. / Handheld 60 hours/load cell 1200 hours continuous.
Accuracy: ±0,1%FC of applied load.
Frequency: 2.4 GHz.
System range: 700 m.
Data rate: 3 Hz up to 200 Hz can be ordered for dynamic load monitoring applications.
Protection: IP65.

... *Read more*


Material: High-quality aircraft grad aluminium.
Temperature range: -10°C up to +50°C.

© November 2026 - All Rights Reserved

LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Crane Scale Radiolink Plus Crosby

Blueprint



Technical data

Part code	Code	WLL (metric) tonnes	Safety factor	Resolution kg	Loading pin Ø mm	A in	B in	C in	D in	E in	F in	G in	Weight lb
16.50RLP1T	RLP1T	1	12:1	0.5	19	8.03	1.69	4.09	5.75	0.96	1.89	0.75	3.31
16.50RLP2T5	RLP2T5	2.5	7:1	1	19	8.03	1.69	4.09	5.75	0.96	1.89	0.75	3.31
16.50RLP6T5	RLP6T5	6.5	7:1	1	25	9.8	1.69	4.45	6.5	1.5	2.6	1.26	5.29
16.50RLP12T	RLP12T	12	7:1	2	35	12.01	1.85	4.45	7.6	1.87	-	-	8.16
16.50RLP25T	RLP25T	25	5:1	5	51	13.39	2.36	4.53	8.46	2.17	-	-	11.02
16.50RLP35T	RLP35T	35	5:1	5	57	15.47	2.95	4.96	8.86	2.36	-	-	18.96
16.50RLP55T	RLP55T	55	5:1	10	57	16.69	2.95	7.09	9.06	2.99	-	-	28.66
16.50RLP75T	RLP75T	75	5:1	10	70	18.5	2.95	7.95	10.24	2.99	-	-	35.27
16.50RLP100T	RLP100T	100	5:1	50	83	23.94	3.9	10.04	12.6	4.29	-	-	74.96
16.50RLP150T	RLP150T	150	4:1	50	95	26.38	3.9	11.93	14.17	4.29	-	-	101.41
16.50RLP200T	RLP200T	200	5:1	100	121	27.56	5.67	13.78	13.78	5.71	-	-	180.78
16.50RLP250T	RLP250T	250	4:1	100	127	27.56	5.67	13.78	13.78	5.71	-	-	180.78
16.50RLP300T	RLP300T	300	5:1	100	152	31.73	5.91	16.77	13.78	6.3	-	-	260.15

© November 2026 - All Rights Reserved