LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Subsea Shackle Crosby G-209R

Product information



Design: Deformation and angle indicators forged on the bow. Fatigue rated
... Read more

Material: Forged steel, Quenched & Tempered, with alloy pins.
Marking: CE-mark, WLL
Finish: Galvanized and painted fluorescent yellow.


Safety factor: 5:1

© November 2026 - All Rights Reserved

LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Subsea Shackle Crosby G-209R

Blueprint



Technical data

Part code	WLL (metric) tonnes	Opening mm	Bolt Ø mm	A +/- 6.35 mm in	B in	C in	H in	L in	O in	P in	S in	T in	Weight lb
11.301020872	6.5	36.6	25.4	1.44	1	3.31	5.83	4.02	1.97	2.28	0.67	0.39	3.73
11.301020902	8.5	42.9	28.7	1.69	1.13	3.76	6.57	4.69	1.97	2.4	0.71	0.39	5.71
11.301020932	9.5	46	31.8	1.81	1.25	4.25	7.48	5.16	2.76	3.27	0.71	0.47	8.31
11.301020952	12	51.5	35.1	2.03	1.38	4.69	8.27	5.75	2.76	3.31	0.91	0.47	11.07
11.301020972	13.5	57	38.1	2.24	1.5	5.24	9.17	6.38	2.95	3.58	0.91	0.59	14.66
11.301020992	17	60.5	41.4	2.38	1.63	5.75	10	6.89	2.95	3.66	0.94	0.59	18.92
11.301021102	25	73	51	2.87	2.01	7.01	12.32	8.86	3.54	4.49	1.14	0.69	31.09
11.301021125	35	82.5	57	3.25	2.24	7.76	13.7	9.96	4.17	5.2	1.18	0.79	47.18
11.301021158	55	105	70	4.13	2.76	10.51	17.83	12.87	4.72	5.71	1.77	0.98	94.36

© November 2026 - All Rights Reserved