



Subsea Shackle Crosby G-209R

Product information

Design: Deformation and angle indicators forged on the bow. Fatigue rated [... Read more](#)

Material: Forged steel, Quenched & Tempered, with alloy pins.

Marking: CE-marked, WLL

Finish: Galvanized and painted fluorescent yellow.


Safety factor: 5:1





Subsea Shackle Crosby G-209R

Blueprint



Technical data

Part code	WLL (metric) tonnes	Opening mm	Bolt Ø mm	A +/- 6.35 mm in	B in	C in	H in	L in	O in	P in	S in	T in	Weight lb
11.301020872	6.5	36.6	25.4	1.44	1	3.31	5.83	4.02	1.97	2.28	0.67	0.39	3.73
11.301020902	8.5	42.9	28.7	1.69	1.13	3.76	6.57	4.69	1.97	2.4	0.71	0.39	5.71
11.301020932	9.5	46	31.8	1.81	1.25	4.25	7.48	5.16	2.76	3.27	0.71	0.47	8.31
11.301020952	12	51.5	35.1	2.03	1.38	4.69	8.27	5.75	2.76	3.31	0.91	0.47	11.07
11.301020972	13.5	57	38.1	2.24	1.5	5.24	9.17	6.38	2.95	3.58	0.91	0.59	14.66
11.301020992	17	60.5	41.4	2.38	1.63	5.75	10	6.89	2.95	3.66	0.94	0.59	18.92
11.301021102	25	73	51	2.87	2.01	7.01	12.32	8.86	3.54	4.49	1.14	0.69	31.09
11.301021125	35	82.5	57	3.25	2.24	7.76	13.7	9.96	4.17	5.2	1.18	0.79	47.18
11.301021158	55	105	70	4.13	2.76	10.51	17.83	12.87	4.72	5.71	1.77	0.98	94.36