LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Horizontal Lifting Clamp Terrier FHX/FHSX

Product information



For horizontal lifting and transporting of steel plates and other non-deflecting materials. Jaw openings available from: 0 to 150 mm. Only to be used and only sold in pairs.

Model FHX: Standard clamp

Model FHSX: Clamp with enlarged jaw opening.

- Compact design and high lifting capacity
- Lightweight design for easy handling
- Tough quality heavy duty welded body

... *Read more*


Marking: According to standard, CE-mark, Type, serial number, WLL, Jaw opening.
Temperature range: - 40°C up to +100°C
Standard: EN 13155
Note: Must always be used in pairs (or multiple pairs)
Warning: Hardness level of the material surface may not exceed 37 HrC (345 Hb, 1166 N/mm2)

© November 2026 - All Rights Reserved

LAM-É ST-PIERRE | Lifting Solutions Group
Axel Johnson International

Horizontal Lifting Clamp Terrier FHX/FHSX

Blueprint



Technical data

Part code	Code	WLL (metric) tonnes	Jaw width in	V in	S in	W in	T in	H in	X in	U in	Y in	Weight lb
16.01953100	1 FHX	1	0-1.38	5.51	3.9	0.39	0.98	0.45	2.56	7.4	0.59	5.73
16.01953200	2 FHX	2	0-2.36	7.09	4.65	0.59	1.2	0.77	3.54	11.3	0.63	15.43
16.01954200	2 FHSX	2	0-3.94	7.09	4.72	0.59	1.2	0.77	3.54	15.08	0.59	20.28
16.01953300	3 FHX	3	0-2.36	7.09	4.65	0.79	1.2	0.77	3.54	11.46	0.63	17.64
16.01954300	3 FHSX	3	0-3.94	7.09	4.72	0.79	1.2	0.77	3.54	15.24	0.59	22.05
16.01953400	4 FHX	4	0-2.36	8.66	5.71	0.98	1.2	0.77	4.13	11.97	0.79	28.66
16.01954400	4 FHSX	4	0-3.94	8.66	5.71	0.98	1.2	0.77	4.13	16.3	0.79	33.07
16.01953600	6 FHX	6	0-2.36	8.66	5.71	0.98	1.2	0.77	4.33	12.09	0.79	30.86
16.01954600	6 FHSX	6	0-3.94	8.66	5.71	0.98	1.2	0.77	4.72	16.3	0.79	36.38
16.01953800	8 FHX	8	0-2.36	8.86	5.31	1.38	1.2	0.77	4.72	13.23	1.18	41.89
16.01954800	8 FHSX	8	0-3.94	8.86	5.31	1.38	1.2	0.77	4.72	16.85	1.18	46.3
16.01953010	10 FHX	10	0-2.36	8.86	5.31	1.38	1.2	0.77	4.72	13.23	1.18	41.89
16.01954010	10 FHSX	10	0-3.94	8.86	5.31	1.38	1.2	0.77	4.72	16.85	1.18	48.5
16.01953012	12 FHX	12	0-2.36	8.86	5.31	1.38	1.2	0.77	4.72	13.23	1.18	41.89
16.01954012	12 FHSX	12	0-3.94	8.86	5.31	1.38	1.2	0.77	4.72	16.85	1.18	48.5
16.01953015	15 FHX	15	0-2.36	10.31	5.79	1.38	1.69	0.85	6.3	13.54	1.38	66.14
16.01853820	15 FHSX	15	0-5.91	13.78	9.45	1.38	1.77	1.08	5.51	26.18	1.38	116.85
16.01953025	25 FHX	25	0-2.36	10.31	5.79	1.57	1.69	0.85	6.89	13.74	1.38	72.75

© November 2026 - All Rights Reserved