



LSP Round Sling LX

Product information



LX round slings are made of multiple high-tenacity yarns covered with an endless sheath (type 5). This is then covered with a seamless double sheath of blue nylon, which includes a protective micro-film. A round sling is therefore constructed from a load-bearing polyester or polyethylene yarn that is wound around itself multiple times. The load-bearing yarns never come into contact with the load, and these slings offer greater capacity compared to conventional synthetic slings of similar weight and size.

... [Read more](#)

Material: Nylon, Polyester or Polyethylene

Safety factor: 5:1



LSP Round Sling LX

Technical data

WLL lb
3,000
3,000
3,000
3,000
3,000
3,000
3,000
3,000
3,000
3,000
4,000
4,000
4,000
4,000
4,000
4,000
4,000
4,000
4,000
4,000
4,000
4,000
6,000
6,000
6,000
6,000
6,000
6,000
6,000
6,000
6,000
6,000
6,000
9,000
9,000
9,000
9,000



LSP Round Sling LX

Technical data

	WLL lb
	9,000
	9,000
	9,000
	9,000
	9,000
	12,000
	12,000
	12,000
	12,000
	12,000
	12,000
	12,000
	12,000
	12,000
	14,000
	14,000
	14,000
	14,000
	14,000
	14,000
	14,000
	14,000
	14,000
	14,000
	17,000
	17,000
	17,000
	17,000
	17,000
	17,000
	17,000
	17,000



LSP Round Sling LX

Technical data

	WLL lb
	90,000
	90,000