



LSP Round Sling LXC

Product information



LXC round slings are made of multiple high-tenacity yarns encased in an endless sleeve (Type 5). The entire assembly is covered by a seamless, double-wall blue nylon jacket that includes a protective micro-film. An LXC round sling is therefore constructed from TITAN HMPE load-bearing yarns wound in multiple continuous loops. Since the load-bearing yarns never come into contact with the load, they offer higher capacities compared to conventional synthetic slings of similar weight and size.

... [Read more](#)

Material: Nylon, Titan HMPE

Safety factor: 5:1



LSP Round Sling LXC

Technical data

WLL lb
60,000
70,000
70,000
70,000
70,000
70,000
70,000
70,000
70,000
70,000
85,000
85,000
85,000
85,000
85,000
85,000
85,000
85,000
85,000
85,000
100,000
100,000
100,000
100,000
100,000
100,000
100,000
100,000
100,000
100,000
100,000
125,000
125,000
125,000



LSP Round Sling LXC

Technical data

WLL lb
125,000
125,000
125,000
125,000
125,000
125,000
150,000
150,000
150,000
150,000
150,000
150,000
150,000
150,000
150,000
150,000
175,000
175,000
175,000
175,000
175,000
175,000
175,000
175,000
175,000
200,000
200,000
200,000
200,000
200,000
200,000
200,000
200,000

