



Caldwell Dura-Lite Composite Fixed-Spread Lifting Beam Model 419

Product information



CONSULT OUR REPRESENTATIVES FOR MORE TECHNICAL DETAILS

Model 419 represents their line of Dura-Lite™ fixed spread lifting beams. Constructed from fiber-reinforced polymer composite materials these beams are lightweight, non-conductive, and highly corrosion-resistant, making them ideal for rigorous or corrosive environments. Complies with ASME B30.20, design category B, service class 4

... [Read more](#)

Marking: According to standard, CE-marked
Standard: ASME B30.20



Caldwell Dura-Lite Composite Fixed-Spread Lifting Beam Model 419

Technical data

WLL (metric) tonnes	table.heading.Length_in	Headroom mm	Weight lb
0.25	24	342.9	6
0.25	36	342.9	8
0.25	48	342.9	9.99
0.25	72	419.1	22.99
0.25	96	419.1	30
0.25	120	469.9	69
0.25	44	469.9	82.01
0.5	24	353.06	7.01
0.5	36	353.06	8.99
0.5	48	378.46	11.99
0.5	72	429.26	25
0.5	96	480.06	58
0.5	120	480.06	77.01
1	24	497.84	8.99
1	36	497.84	11
1	48	548.64	19
1	72	599.44	46.01
1	96	599.44	61.99
2	24	556.26	14.99
2	36	612.14	24.01
2	48	657.86	43.01
2	72	657.86	55.01
3	24	632.46	21.01
3	36	632.46	24.01
3	48	675.64	43.01