







TRANSPORT CHAIN - GRADE 70

FEATURES

The grade 70 chains are extremely strong for their light weight and are mostly used for loading on platform trucks in the transportation field.

They are also widely used on farms, for wood transportation, towing and construction. The ratio of great strength versus the weight of the grade 70 chains is achieved through a special heat treatment. They resist wear thanks to their exceptional hardness properties.



MATERIAL:

• High-carbon steel, heat treated

FINITION:

• Zinc plated with gold chromate finish

Sold at the foot or barrel

ACCESSORIES:

- Can be supplied in assembly with forged shackle hooks at each end and other required accessories.
- Meets ASTM & NACM standards and FMCSA & CVSA requirements

PERMANENT IDENTIFICATION ON CHAIN, EMBOSSED WITH G70, PLUS 3 LETTER TRACE CODE, 100% PROOF TESTED

DIMENSIONS														
CHAIN		GRADE	INSIDE DIMENSIONS				STOCK NO.	FEET PER	WEIGHT (LBS/FT.)		WORKING LOAD LIMIT		(APPROX) NUMBER OF	
DIAMETER (A)			Length		Width		STOCK NO.	DRUM					LINK PER FEET	
in	mm		in	mm	in	mm			lb	kg	lb	kg		
1/4	7	70	0.84	21.3	0.47	11.9	GR701/4CM-4A	400	0.76	0.34	3,150	1,430	14.30	
5/16	8	70	1.10	27.9	0.50	12.7	GR705/16CM-4A	550	0.97	0.44	4,700	2,130	10.90	
3/8	10	70	1.38	35.0	0.60	15.2	GR703/8CM-4A	400	1.37	0.62	6,600	2,990	8.73	
1/2	13	70	1.56	39.6	0.73	18.5	GR701/2CM-4A	200	2.42	1.10	11,300	5,130	7.70	
Safety F	Safety Factor: 4/1													

chain is embossed "C70"



